



MOBOTIX Price List

01.04.2016 English EUR

All prices are Manufacturer's suggested retail prices, net, ex works. Information subject to change without notice.
The dimensions and weights of the articles apply to the product ready for shipping (i.e., including the packaging).



Professional Video Systems Outdoor

All prices are Manufacturer's suggested retail prices, net, ex works. Information subject to change without notice.
HS = Harmonized System Code DG = Discount Group

M15 AllroundDual Camera

Robust. Most Advanced Design.

The M15 works with two light-sensitive image sensors and two lenses that allow the camera to generate sharp color videos and high-contrast B&W videos, even in dark situations. The electronic switching between the day and night system is automatic, with no moving parts and is based on light conditions to ensure reliable operation at any temperature and in any weather.

By design, the M15 is the most robust of the entire MOBOTIX range of products. With an IP66 weatherproof rating, it can withstand extreme temperatures and the harshest of conditions.

The sensor modules need to be ordered separately (apart from the M15 complete sets), are pre-focused at the factory and can be supplied in any desired combination.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-M15D-Sec-DNIGHT-D22N22-6MP-F1.8	4047438023009	34,5 cm	C	1.248,00 EUR
	M15 Complete Cam 6MP, 2x L22-F1.8, Day & Night	85258091	34,0 cm		
	IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x L22/B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: sensor modules (2x), speaker (microphone via sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	2.510 g	20,0 cm		
	MX-M15D-Sec-DNIGHT-D43N43-6MP-F1.8	4047438023023	34,5 cm	C	1.248,00 EUR
	M15 Complete Cam 6MP, 2x L43-F1.8, Day & Night	85258091	34,0 cm		
	IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x L43/B079 wide-angle (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: sensor modules (2x), speaker (microphone via sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	2.510 g	20,0 cm		
	MX-M15D-Sec-DNIGHT-D25N25-F1.8	4047438022200	34,5 cm	C	1.148,00 EUR
	M15 5MP, 2x L25-F1.8 (Day & Night)	85258091	34,0 cm		
	IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/2.5" CMOS, 5 megapixels, 1x color (day) and 1x B/W (night) • HD Premium lenses (via sensor module): 2x L25 super wide-angle (f/1.8, horizontal image angle 82°) • Max. image size (per image sensor): 5MP (2592 x 1944 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • System components: sensor modules (2x), speaker (microphone via sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	2.510 g	20,0 cm		
	MX-M15D-Sec-DNIGHT-D38N38-F1.8	4047438023887	34,5 cm	C	1.148,00 EUR
	M15 5MP, 2x L38-F1.8 (Day & Night)	85258091	34,0 cm		
	IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/2.5" CMOS, 5 megapixels, 1x color (day) and 1x B/W (night) • Lenses (via sensor module): 2x HD Premium lens L38 wide-angle (f/1.8, horizontal image angle 55°) • Max. image size (per image sensor): 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • System components: sensor modules (2x), speaker (microphone via sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	2.510 g	20,0 cm		

**MX-M15D-Sec-DNight-D51N51-F1.8****M15 5MP, 2x L51-F1.8 (Day & Night)**

IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/2.5" CMOS, 5 megapixels, 1x color (day) and 1x B/W (night) • Lenses (via sensor module): 2x HD Premium lens L51 wide-angle (f/1.8, horizontal image angle 40°) • Max. image size (per image sensor): 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • System components: sensor modules (2x), speaker (microphone via sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

4047438023894	34,5 cm	C	1.148,00	EUR
85258091	34,0 cm			
2.510 g	20,0 cm			

**MX-M15D-Sec-DNight-D76N76-F1.8****M15 5MP, 2x L76-F1.8 (Day & Night)**


IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/2.5" CMOS, 5 megapixels, 1x color (day) and 1x B/W (night) • Lenses (via sensor module): 2x HD Premium lens L76 tele (f/1.8, horizontal image angle 27°) • Max. image size (per image sensor): 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • System components: sensor modules (2x), speaker (microphone via sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

4047438023900	34,5 cm	C	1.148,00	EUR
85258091	34,0 cm			
2.510 g	20,0 cm			

**MX-M15D-Sec-DNight-D160N160-F1.8****M15 5MP, 2x L160-F1.8 (Day & Night)**

IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/2.5" CMOS, 5 megapixels, 1x color (day) and 1x B/W (night) • Lenses (via sensor module): 2x HD Premium lens L160 tele (f/1.8, horizontal image angle 13°) • Max. image size (per image sensor): 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • System components: sensor modules (2x), speaker (microphone via sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

4047438023917	34,5 cm	C	1.148,00	EUR
85258091	34,0 cm			
2.510 g	20,0 cm			

**MX-M15D-Sec****M15 Body, For 1-2 Sensor Modules (Day/Night)**

M15 camera module for connecting one or two sensor modules (to be ordered individually) • Image sensor options (via sensor module): 5 or 6 megapixels, color (day) and/or B/W (night) • Lens options (via sensor module): L10/B016 to L270/B500, horizontal image angle 180° to 8° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker (microphone via sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438018258	34,5 cm	C	852,00	EUR
85258091	34,0 cm			
2.100 g	20,0 cm			

M15 AllroundDual Camera (SUP)

Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. These products can also be ordered from the standard program as individual components for self-assembly.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-M15D-Sec-DNight-D20N20-6MP-F1.8	4047438022996	34,5 cm	C	1.278,00 EUR
	M15 Complete Cam 6MP, 2x L20-F1.8, Day & Night	85258091	34,0 cm		
	IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x L20/B036 ultra wide-angle (f/1.8, horizontal image angle 103°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: sensor modules (2x), speaker (microphone via sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	2.510 g	20,0 cm		
	MX-M15D-Sec-DNight-D32N32-6MP-F1.8	4047438023016	34,5 cm	C	1.278,00 EUR
	M15 Complete Cam 6MP, 2x L32-F1.8, Day & Night	85258091	34,0 cm		
	IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x L32/B061 wide-angle (f/1.8, horizontal image angle 60°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: sensor modules (2x), speaker (microphone via sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	2.510 g	20,0 cm		
	MX-M15D-Sec-DNight-D65N65-6MP-F1.8	4047438023030	34,5 cm	C	1.278,00 EUR
	M15 Complete Cam 6MP, 2x L65-F1.8, Day & Night	85258091	34,0 cm		
	IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x L65/B119 tele (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: sensor modules (2x), speaker (microphone via sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	2.510 g	20,0 cm		
	MX-M15D-Sec-DNight-D135N135-6MP-F1.8	4047438023047	34,5 cm	C	1.278,00 EUR
	M15 Complete Cam 6MP, 2x L135-F1.8, Day & Night	85258091	34,0 cm		
	IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x L135/B237 tele (f/1.8, horizontal image angle 15°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: sensor modules (2x), speaker (microphone via sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	2.510 g	20,0 cm		

S15 FlexMount Camera

Flexible. Virtually Invisible Camera System.

With the S15, one or two sensor modules are each connected to a concealable camera housing via up to three meter long cables. Thanks to its separation of camera housing and image sensor/lens the S15 offers a broad range of installation and application scenarios. The sensor modules need to be ordered separately (apart from the S15 complete sets), are pre-focused at the factory and can be supplied in any desired combination (2x optical, thermal/optical, 2x thermal). The S15M is a single lens camera. It can be mounted in a concealed manner behind a wall or ceiling panel, to a stainless steel plate etc.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-S15D-Set1-6MP	4047438023313	34,0 cm	C	898,00 EUR
	S15 Complete Cam, Set 1, 6MP, 1x L10, Day	85258091	34,0 cm		
	S15 camera module (body) • 1x sensor module with HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 1x replacement dome • IP66 • Optional connection of a second sensor module (incl. Thermal) or MOBOTIX Door Station modules	1.670 g	16,0 cm		
	MX-S15D-Set2-6MP	4047438023320	34,0 cm	C	1.198,00 EUR
	S15 Complete Cam, Set 2, 6MP, 2x L10, Day	85258091	34,0 cm		
	S15 IP camera module (body) • 2x sensor module with HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 2x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66 • Connection of MOBOTIX Door Station modules	1.670 g	16,0 cm		
	MX-S15D-Set3-6MP	4047438023337	34,0 cm	C	1.198,00 EUR
	S15 Complete Cam, Set 3, 6MP, 2x L10, Day & Night	85258091	34,0 cm		
	S15 camera module (body) • 1x sensor module with HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor module with HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66 • Connection of MOBOTIX Door Station modules	1.670 g	16,0 cm		
	MX-S15-D016	4047438026833	23,0 cm	C	798,00 EUR
	S15M Complete Cam 6MP, 1.6 mm, Tag	85258091	19,2 cm		
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65/IK06, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory) • Connection of MOBOTIX Door Station modules	720 g	8,3 cm		
	MX-S15-N016	4047438026840	23,0 cm	C	798,00 EUR
	S15M Complete Cam 6MP, 1.6 mm, Night	85258091	19,2 cm		
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, BW (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65/IK06, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory) • Connection of MOBOTIX Door Station modules	720 g	8,3 cm		
	MX-S15D-Sec	4047438017725	23,0 cm	C	648,00 EUR
	S15 Body, For 1–2 Sensor Modules (Day/Night/Thermal)	85258091	19,2 cm		
	S15 camera module (body) for connecting one or two sensor modules (to be ordered individually) • Image sensor options (via sensor module): 6 megapixels, color (day) and/or B/W (night) and/or thermal • Lens options (via optical sensor module): L10/B016 to L270/B500, horizontal image angle 180° to 8° • IP65, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: 2x MOBOTIX sensor cable, Ethernet 10/100 (RJ45 and LSA), MxBus, USB, Audio I/O; RS232 via MX Interface Box • Connection of MOBOTIX Door Station modules	704 g	8,3 cm		

	MX-S15D-Set1	4047438019880	34,0 cm	C	848,00	EUR
	S15 Complete Set 1, 5MP (1x Day)	85258091	34,0 cm			
	FlexMount S15 IP camera module (body) • 1x sensor module Hemispheric L12, white, 5MP color sensor (day) • 1x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 1x replacement dome	1.670 g	16,0 cm			
	MX-S15D-Set2	4047438019897	34,0 cm	C	1.098,00	EUR
	S15 Complete Set 2, 5MP (2x Day)	85258091	34,0 cm			
	FlexMount S15 IP camera module (body) • 2x sensor module Hemispheric L12, white, 5MP color sensor (day) • 2x sensor cable 2 m/6.6 ft • 2x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome	1.670 g	16,0 cm			
	MX-S15D-Set3	4047438019903	34,0 cm	C	1.098,00	EUR
	S15 Complete Set 3, 5MP (Day & Night)	85258091	34,0 cm			
	FlexMount S15 IP camera module (body) • 1x sensor module Hemispheric L12, white, 5MP color sensor (day) • 1x sensor module Hemispheric L12, white, 5MP B/W sensor (night) • 2x sensor cable 2 m/6.6 ft • 2x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome	1.670 g	16,0 cm			

D15 DualDome Camera

Multifunctional. Twice As Vigilant.

The D15 is a DualDome camera with two lens units providing a wide range of fully adjustable viewing options. The D15 is completely modular, available as standard DualDome, as 180° pano model offering a super-wide panorama view or as day-night model.

The D15 is able to secure two different areas simultaneously. The key advantage of the D15 is its manually adjustable lens configuration and the complete modular setup. Once installed, the lens units can be fixed into any position.

The D15 can be used with one or two day or night sensors or a day/night sensor combination. The D15 lens units for self-assembly can be selected at customer's option. The Day & Night and Pano/180° models need special lens carriers which are also available here (see D15 Lens Units).

Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
 MX-D15Di-Sec D15 Body, For 1–2 Lens Units/Carrier (Day/Night/180°) IP camera module for connecting one or two lens units or a double lens carrier FIX/PAN (to be ordered individually) • Image sensor options (via lens unit/carrier): 6 megapixels, color (day) and/or B/W (night) • Lens options (via lens unit): L20/B036 to L135/B237, horizontal image angle 103° to 15° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Incl. two lens covers (1x Standard, 1x XL) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438017978	34,5 cm	C	948,00 EUR
	85258091	34,0 cm		
	1.980 g	16,0 cm		

D15 DualDome Camera (SUP)

Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. These products can also be ordered from the standard program as individual components for self-assembly.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-D15Di-Sec-DNight-D20N20-FIX-6MP-F1.8	4047438023238	34,5 cm	C	1.278,00 EUR
	D15 Complete Cam 6MP, 2x L20-F1.8, Day & Night	85258091	34,0 cm		
	IP camera with two parallel aligned lenses • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x L20/B036 ultra wide-angle (f/1.8, horizontal image angle 103°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	1.980 g	16,0 cm		
	MX-D15Di-Sec-DNight-D22N22-FIX-6MP-F1.8	4047438023245	34,5 cm	C	1.278,00 EUR
	D15 Complete Cam 6MP, 2x L22-F1.8, Day & Night	85258091	34,0 cm		
	IP camera with two parallel aligned lenses • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x L22/B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	1.980 g	16,0 cm		
	MX-D15Di-Sec-DNight-D32N32-FIX-6MP-F1.8	4047438023252	34,5 cm	C	1.278,00 EUR
	D15 Complete Cam 6MP, 2x L32-F1.8, Day & Night	85258091	34,0 cm		
	IP camera with two parallel aligned lenses • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x L32/B061 wide-angle (f/1.8, horizontal image angle 60°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	1.980 g	16,0 cm		
	MX-D15Di-Sec-DNight-D43N43-FIX-6MP-F1.8	4047438023269	34,5 cm	C	1.278,00 EUR
	D15 Complete Cam 6MP, 2x L43-F1.8, Day & Night	85258091	34,0 cm		
	IP camera with two parallel aligned lenses • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x L43/B079 wide-angle (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	1.980 g	16,0 cm		
	MX-D15Di-Sec-DNight-D65N65-FIX-6MP-F1.8	4047438023276	34,5 cm	C	1.278,00 EUR
	D15 Complete Cam 6MP, 2x L65-F1.8, Day & Night	85258091	34,0 cm		
	IP camera with two parallel aligned lenses • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x L65/B119 tele (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	1.980 g	16,0 cm		

	MX-D15Di-Sec-DNIGHT-D135N135-FIX-6MP-F1.8 D15 Complete Cam 6MP, 2x L135-F1.8, Day & Night IP camera with two parallel aligned lens units • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x L135/B237 tele (f/1.8, horizontal image angle 15°) • Equipment line: Secure • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	4047438023283 85258091 1.980 g	34,5 cm 34,0 cm 16,0 cm	C	1.278,00 EUR
	MX-D15Di-Sec-180-6MP-F1.8 D15 Complete Cam 2x 6MP, Panorama 180°, Day IP camera with double lens unit • 2 Moonlight sensors day, 6MP (3072 x 2048) • HD premium lenses: 2x L22/B041 super wide-angle (horiz. image angle 180°) • Max. image size: 2x 6MP (6144 x 2048 Pixel) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount, IP66/IK10+ with Vandalism Set, each -30 bis 60 °C (-22 to 140° F) • Internal DVR: 4 GB microSD • Speaker, microphone, PIR sensor, temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0,5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	4047438023290 85258091 1.980 g	34,5 cm 34,0 cm 16,0 cm	C	1.278,00 EUR
	MX-D15Di-Sec-Night-180-6MP-F1.8 D15 Complete Cam 2x 6MP, Panorama 180°, Night IP camera with double lens unit • 2 Moonlight sensors night, 6MP (3072 x 2048) • HD premium lenses: 2x L22/B041 super wide-angle (horiz. image angle 180°) • Max. image size: 2x 6MP (6144 x 2048 Pixel) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount, IP66/IK10+ with Vandalism Set, each -30 bis 60 °C (-22 to 140° F) • Internal DVR: 4 GB microSD • Speaker, microphone, PIR sensor, temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0,5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	4047438023306 85258091 1.980 g	34,5 cm 34,0 cm 16,0 cm	C	1.278,00 EUR
	MX-D15Di-Sec-DNIGHT-D23N23-FIX-F1.8 D15, 2x 5MP, 2x L23-F1.8 (Day & Night) IP camera with two parallel aligned lens units • Image sensors: 1/2.5" CMOS, 5 megapixels, 1x day and 1x night • HD Premium lenses (via sensor module): 2x L23 wide-angle (f/1.8, horizontal image angle 92°) • Max. image size (per image sensor): 5MP (2592 x 1944 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438022392 85258091 1.980 g	34,5 cm 34,0 cm 16,0 cm	C	1.148,00 EUR
	MX-D15Di-Sec-DNIGHT-D25N25-FIX-F1.8 D15, 2x 5MP, 2x L25-F1.8 (Day & Night) IP camera with fixed lens units • Image sensors: 1/2.5" CMOS, 5 megapixels, 1x color (day) and 1x B/W (night) • HD Premium lenses: 2x L25 super wide-angle (f/1.8, horizontal image angle 82°) • Max. image size (per image sensor): 5MP (2592 x 1944 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438022194 85258091 1.980 g	34,5 cm 34,0 cm 16,0 cm	C	1.148,00 EUR
	MX-D15Di-Sec-DNIGHT-D38N38-FIX-F1.8 D15, 2x 5MP, 2x L38-F1.8 (Day & Night) IP camera with fixed lens units • Image sensors: 1/2.5" CMOS, 5 megapixels, 1x color (day) and 1x B/W (night) • HD Premium lenses: 2x L38 wide-angle (f/1.8, horizontal image angle 55°) • Max. image size (per image sensor): 5MP (2592 x 1944 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438024044 85258091 1.980 g	34,5 cm 34,0 cm 16,0 cm	C	1.148,00 EUR

	MX-D15Di-Sec-DNIGHT-D51N51-FIX-F1.8	4047438024051	34,5 cm	C	1.148,00	EUR
	D152x 5MP, 2x L51-F1.8 (Day & Night)	85258091	34,0 cm			
	IP camera with fixed lens units • Image sensors: 1/2.5" CMOS, 5 megapixels, 1x color (day) and 1x B/W (night) • HD Premium lenses: 2x L51 wide-angle (f/1.8, horizontal image angle 40°) • Max. image size (per image sensor): 5MP (2592 x 1944 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	1.980 g	16,0 cm			
	MX-D15Di-Sec-DNIGHT-D76N76-FIX-F1.8	4047438024068	34,5 cm	C	1.148,00	EUR
	D15, 2x 5MP, 2x L76-F1.8 (Day & Night)	85258091	34,0 cm			
	IP camera with fixed lens units • Image sensors: 1/2.5" CMOS, 5 megapixels, 1x color (day) and 1x B/W (night) • HD Premium lenses: 2x L76 tele (f/1.8, horizontal image angle 27°) • Max. image size (per image sensor): 5MP (2592 x 1944 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	1.980 g	16,0 cm			
	MX-D15Di-Sec-DNIGHT-D160N160-FIX-F1.8	4047438024075	34,5 cm	C	1.148,00	EUR
	D15, 2x 5MP, 2x L160-F1.8 (Day & Night)	85258091	34,0 cm			
	IP camera with fixed lens units • Image sensors: 1/2.5" CMOS, 5 megapixels, 1x color (day) and 1x B/W (night) • HD Premium lenses: 2x L160 tele (f/1.8, horizontal image angle 13°) • Max. image size (per image sensor): 5MP (2592 x 1944 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	1.980 g	16,0 cm			
	MX-D15Di-Sec-180	4047438022095	34,5 cm	C	1.148,00	EUR
	D15, 2x 5MP, Panorama 180° (Day)	85258091	34,0 cm			
	IP camera with 180° double lens unit • Image sensors: 1/2.5" CMOS, 5 megapixels, 2x color (day) • Lenses: 2x L23 super wide-angle, horizontal image angle 180° • Max. image size (with two images sensors): 2x 5MP (5184 x 1944 pixels) • Operating conditions: IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	1.980 g	16,0 cm			
	MX-D15Di-Sec-Night-180	4047438022101	34,5 cm	C	1.148,00	EUR
	D15, 2x 5MP, Panorama 180° (Night)	85258091	34,0 cm			
	IP camera with 180° double lens unit • Image sensors: 1/2.5" CMOS, 5 megapixels, 2x B/W (night) • Lenses: 2x L23 super wide-angle, horizontal image angle 180° • Max. image size (with two images sensors): 2x 5MP (5184 x 1944 pixels) • Operating conditions: IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	1.980 g	16,0 cm			

Q25 Hemispheric Camera

Elegant. Allround Secure.

Setting a new benchmark in design, this all-in-one Hemispheric camera offers a super-wide 360° allround view, in high resolution. Easily replacing four standard CCTV cameras, just one Q25 captures an entire room. The Q25 is highly discreet and fits in everywhere – both indoors and outdoors. Available in both day and night models, which cater to the most challenging lighting conditions and a wide range of applications.

MOBOTIX Panorama Image Technology

Unlike competitors, hemispheric distortion correction takes place in the MOBOTIX camera and not later on the computer. This drastically reduces the image data before it is transferred and saved. This “decentralized” MOBOTIX solution lowers the volume of network traffic and allows dozens of hemispheric cameras to be displayed on a computer or smartphone.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-Q25-D016	4047438025829	30,5 cm	C	798,00 EUR
	Q25 Complete Cam 6MP, 1.6 mm, Tag	85258091	23,5 cm		
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory) • Color: white	1.630 g	16,0 cm		
	MX-Q25-N016	4047438025843	30,5 cm	C	798,00 EUR
	Q25 Complete Cam 6MP, 1.6 mm, Night	85258091	23,5 cm		
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory) • Color: white	1.630 g	16,0 cm		
	MX-Q25M-Sec-D12	4047438019408	30,5 cm	C	748,00 EUR
	Q25 5MP, Hemispheric L12 (Day)	85258091	23,5 cm		
	IP camera with image sensor and fisheye lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L12 hemispheric (horizontal image angle 180°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX -232-IO-Box	1.630 g	16,0 cm		
	MX-Q25M-Sec-D25	4047438019422	30,5 cm	C	748,00 EUR
	Q25 5MP, L25 (Day)	85258091	23,5 cm		
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L25 super wide-angle (horizontal image angle 82°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX -232-IO-Box	1.630 g	16,0 cm		
	MX-Q25M-Sec-Night-N12	4047438019439	30,5 cm	C	748,00 EUR
	Q25 5MP, Hemispheric L12 (Night)	85258091	23,5 cm		
	IP camera with image sensor and fisheye lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L12 hemispheric (horizontal image angle 180°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX -232-IO-Box	1.630 g	16,0 cm		
	MX-Q25M-Sec-Night-N25	4047438019453	30,5 cm	C	748,00 EUR
	Q25 5MP, L25 (Night)	85258091	23,5 cm		
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L25 super wide-angle (horizontal image angle 82°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX -232-IO-Box	1.630 g	16,0 cm		

**MX-Q25M-Sec-D12-BL****Q25 5MP, Hemispheric L12 (Day), Black**

IP camera with image sensor and fisheye lens • Black camera housing • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L12 hemispheric (horizontal image angle 180°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX-232-IO-Box

4047438019415	30,5 cm	C	748,00	EUR
85258091	23,5 cm			
1.630 g	16,0 cm			

**MX-Q25M-Sec-Night-N12-BL****Q25 5MP, Hemispheric L12 (Night), Black**

IP camera with image sensor and fisheye lens • Black camera housing • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L12 hemispheric (horizontal image angle 180°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX-232-IO-Box

4047438019446	30,5 cm	C	748,00	EUR
85258091	23,5 cm			
1.630 g	16,0 cm			

Q25 Hemispheric Camera (SUP)

Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-Q25-D016-b	4047438025867	30,5 cm	C	898,00 EUR
	Q25 Complete Cam 6MP, 1.6 mm, Tag, Black	85258091	23,5 cm		
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory) • Color: black	1.630 g	16,0 cm		
	MX-Q25-N016-b	4047438025874	30,5 cm	C	898,00 EUR
	Q25 Complete Cam 6MP, 1.6 mm, Night, Black	85258091	23,5 cm		
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory) • Color: black	1.630 g	16,0 cm		

M25 Allround Camera

Tough. For Any Environment.

Designed and engineered to withstand the most demanding of conditions, featuring high tolerance and an IP66 rating. The M25 features the 6MP technology and is highly adaptive as to where it can be deployed, thanks to the wide choice of available lenses. It is possible to identify license plates and people even at distances of more than 70 meters/230 ft. thanks to the B500 (8°) lens that can be used with the M25 and the high-resolution 6MP sensor.

The M25 is equipped with either a color (day) or a black and white (night) image sensor and can be fitted with separately available lenses with horizontal image angles of 8° to 103°.

Every M25 comes with a VarioFlex mount for fast and easy installation on walls, ceilings and poles (also see: Pole Mount MX-MH-SecureFlex-ESWS).

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-M25-D016	4047438024914	30,5 cm	C	798,00 EUR
	M25 Complete Cam 6MP, 1.6 mm, Tag	85258091	23,5 cm		
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm		
	MX-M25-BOD1	4047438024891	30,5 cm	C	738,00 EUR
	M25 Body 6MP, Day	85258091	23,5 cm		
	IP camera module (body) with 6 Megapixel Moonlight Sensor, color (day) • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens MX-B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm		
	MX-M25-BOD1-N	4047438024907	30,5 cm	C	738,00 EUR
	M25 Body 6MP, Night	85258091	23,5 cm		
	IP camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens MX-B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm		
	MX-M25M-Sec-D12	4047438019255	30,5 cm	C	748,00 EUR
	M25 5MP, Hemispheric L12 (Day)	85258091	23,5 cm		
	IP camera with image sensor and fisheye lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L12 Hemispheric, horizontal image angle 180° • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX-232-IO-Box	2.000 g	16,0 cm		
	MX-M25M-Sec-D23-F1.8	4047438021371	30,5 cm	C	748,00 EUR
	M25 5MP, L23-F1.8 (Day)	85258091	23,5 cm		
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L23 (f/1.8) super wide-angle (horizontal image angle 92°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm		

	MX-M25M-Sec-D25-F1.8	4047438021821	30,5 cm	C	748,00	EUR
	M25 5MP, L25-F1.8 (Day)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L25 (f/1.8) super wide-angle (horizontal image angle 82°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			
	MX-M25M-Sec-D38-F1.8	4047438021388	30,5 cm	C	748,00	EUR
	M25 5MP, L38-F1.8 (Day)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L38 (f/1.8) wide-angle (horizontal image angle 55°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			
	MX-M25M-Sec-D51-F1.8	4047438021395	30,5 cm	C	748,00	EUR
	M25 5MP, L51-F1.8 (Day)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L51 (f/1.8) wide-angle (horizontal image angle 40°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			
	MX-M25M-Sec-D76-F1.8	4047438021401	30,5 cm	C	748,00	EUR
	M25 5MP, L76-F1.8 (Day)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L76 (f/1.8) telephoto (horizontal image angle 27°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			
	MX-M25M-Sec-D160-F1.8	4047438021418	30,5 cm	C	748,00	EUR
	M25 5MP, L160-F1.8 (Day)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L160 (f/1.8) telephoto (horizontal image angle 13°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			
	MX-M25M-Sec-D320	4047438019507	30,5 cm	C	748,00	EUR
	M25 5MP, L320 (Day)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L320 super-telephoto, horizontal image angle 7° • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft, extended lens cover • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX-232-IO-Box	2.000 g	16,0 cm			
	MX-M25M-Sec-CSVario	4047438019248	30,5 cm	C	848,00	EUR
	M25 5MP, CSVario (Day)	85258091	23,5 cm			
	IP camera with image sensor and CSVario lens (CS mount) • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: CSVario, horizontal image angle 28° to 58° (manually adjustable) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to +50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft, extended lens cover • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX-232-IO-Box	2.000 g	16,0 cm			

	MX-M25M-Sec	4047438019231	30,5 cm	C	688,00	EUR
	M25 5MP Body (Day)	85258091	23,5 cm			
	IP camera module (body) with image sensor, lens to be ordered individually • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens options: L12to L320, horizontal image angle 180° to 7° • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to +50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX-232-IO-Box	2.000 g	16,0 cm			
	MX-M25M-Sec-Night-N23-F1.8	4047438021432	30,5 cm	C	748,00	EUR
	M25 5MP, L23-F1.8 (Night)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L23 (f/1.8) super wide-angle (horizontal image angle 92°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to +50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			
	MX-M25M-Sec-Night-N25-F1.8	4047438021838	30,5 cm	C	748,00	EUR
	M25 5MP, L25-F1.8 (Night)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L25 (f/1.8) super wide-angle (horizontal image angle 82°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to +50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX-232-IO-Box	2.000 g	16,0 cm			
	MX-M25M-Sec-Night-N38-F1.8	4047438021449	30,5 cm	C	748,00	EUR
	M25 5MP, L38-F1.8 (Night)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L38 (f/1.8) wide-angle (horizontal image angle 55°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to +50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			
	MX-M25M-Sec-Night-N51-F1.8	4047438021456	30,5 cm	C	748,00	EUR
	M25 5MP, L51-F1.8 (Night)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L51 (f/1.8) wide-angle (horizontal image angle 40°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to +50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			
	MX-M25M-Sec-Night-N76-F1.8	4047438021463	30,5 cm	C	748,00	EUR
	M25 5MP, L76-F1.8 (Night)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L76 (f/1.8) telephoto (horizontal image angle 27°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to +50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			
	MX-M25M-Sec-Night-N160-F1.8	4047438021470	30,5 cm	C	748,00	EUR
	M25 5MP, L160-F1.8 (Night)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L160 (f/1.8) telephoto (horizontal image angle 13°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to +50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			

	MX-M25M-Sec-Night-N320	4047438019651	30,5 cm	C	748,00	EUR
	M25 5MP, L320 (Night)	85258091	23,5 cm			
	IP camera with image sensor and fisheye lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L320 super-telephoto, horizontal image angle 7° • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to +50° C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX-232-IO-Box	2.000 g	16,0 cm			
	MX-M25M-Sec-Night-CSVario	4047438019330	30,5 cm	C	848,00	EUR
	M25 5MP, CSVario (Night)	85258091	23,5 cm			
	IP camera with image sensor and CSVario lens (CS mount) • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: CSVario, horizontal image angle 28° to 58° (manually adjustable) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to +50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft, extented lens cover • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX-232-IO-Box	2.000 g	16,0 cm			
	MX-M25M-Sec-Night	4047438019323	30,5 cm	C	688,00	EUR
	M25 5MP Body (Night)	85258091	23,5 cm			
	IP camera module with image sensor (body), lens to be ordered individually • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens options: L12 to L320 • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to +50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX-232-IO-Box	2.000 g	16,0 cm			
	MX-M25M-Sec-Night-N12	4047438019347	30,5 cm	C	748,00	EUR
	M25 5MP, Hemispheric L12 (Night)	85258091	23,5 cm			
	IP camera with image sensor and fisheye lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L12 Hemispheric, horizontal image angle 180° • Max. image size: 5 MP (2592 x 1944 pixels) • Operating conditions: IP66, -30 to +50° C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Speaker, microphone, temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX-232-IO-Box	2.000 g	16,0 cm			

M25 Allround Camera (SUP)

Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. Many products of the supplemental program can be ordered from the standard program as individual components for self-assembly.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
 	MX-M25-D036	4047438024778	30,5 cm	C	828,00 EUR
	M25 Complete Cam 6MP, 3.6 mm, Day	85258091	23,5 cm		
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • Ultra Wide Lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm		
 	MX-M25-D041	4047438024785	30,5 cm	C	828,00 EUR
	M25 Complete Cam 6MP, 4.1 mm, Day	85258091	23,5 cm		
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • Super Wide Lens B041 (focal length 4.1 mm, f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm		
 	MX-M25-D061	4047438024792	30,5 cm	C	828,00 EUR
	M25 Complete Cam 6MP, 6.1 mm, Day	85258091	23,5 cm		
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • Wide Lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm		
 	MX-M25-D079	4047438024808	30,5 cm	C	828,00 EUR
	M25 Complete Cam 6MP, 7.9 mm, Day	85258091	25,5 cm		
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • Standard Lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm		
 	MX-M25-D119	4047438024815	30,5 cm	C	828,00 EUR
	M25 Complete Cam 6MP, 11.9 mm, Day	85258091	23,5 cm		
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • Tele Lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm		
 	MX-M25-D237	4047438024822	30,5 cm	C	828,00 EUR
	M25 Complete Cam 6MP, 23.7 mm, Day	85258091	23,5 cm		
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • Distant Tele Lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm		
 	MX-M25-D500	4047438024952	30,5 cm	C	858,00 EUR
	M25 Complete Cam 6MP, 50 mm, Day	85258091	23,5 cm		
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • Super Tele Lens B500 (focal length 50 mm, f/1.8, 8° x 6°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm		

	MX-M25-N016	4047438024921	30,5 cm	C	828,00	EUR
	M25 Complete Cam 6MP, 1.6 mm, Night	85258091	23,5 cm			
	Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			
	MX-M25-N036	4047438024839	30,5 cm	C	828,00	EUR
	M25 Complete Cam 6MP, 3.6 mm, Night	85258091	23,5 cm			
	IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Ultra Wide Lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			
	MX-M25-N041	4047438024846	30,5 cm	C	828,00	EUR
	M25 Complete Cam 6MP, 4.1 mm, Night	85258091	23,5 cm			
	IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Super Wide Lens B041 (focal length 4.1 mm, f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			
	MX-M25-N061	4047438024853	30,5 cm	C	828,00	EUR
	M25 Complete Cam 6MP, 6.1 mm, Night	85258091	23,5 cm			
	IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Wide Lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			
	MX-M25-N079	4047438024860	30,5 cm	C	828,00	EUR
	M25 Complete Cam 6MP, 7.9 mm, Night	85258091	23,5 cm			
	IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Standard Lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			
	MX-M25-N119	4047438024877	30,5 cm	C	828,00	EUR
	M25 Complete Cam 6MP, 11.9 mm, Night	85258091	23,5 cm			
	IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Tele Lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			
	MX-M25-N237	4047438024884	30,5 cm	C	828,00	EUR
	M25 Complete Cam 6MP, 23.7 mm, Night	85258091	23,5 cm			
	IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Distant Tele Lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			
	MX-M25-N500	4047438024969	30,5 cm	C	858,00	EUR
	M25 Complete Cam 6MP, 50 mm, Night	85258091	23,5 cm			
	IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Super Tele Lens B500 (focal length 50 mm, f/1.8, 8° x 6°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	2.000 g	16,0 cm			

D25 Dome Camera

Traditional Design. Innovative Technology.

Elegance and discreetness based on cutting-edge technology: Up to 30 HiRes images per second and excellent image quality even under poor illumination. The MOBOTIX D25 is perfectly suited for any task. Exchangeable lenses and various mounting and configuration options, including Vandalism Set, support countless applications.

With the D25 series, MOBOTIX offers extremely compact, versatile and cost-effective dome cameras with an integrated video sensor and longterm internal storage on a microSD card. Different premium lenses with image angles from 15° to 103° are currently available (B237 to B036)

The D25 models are completely dust-proof and resistant to water jets (IP65). The D25 Wall Mount (accessory) makes the camera suited for outdoor use and for installation over surface-mounted sockets so that the cabling remains thoroughly concealed.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-D25-BOD1	4047438025249	30,5 cm	C	738,00 EUR
	D25 Body 6MP, Day	85258091	23,5 cm		
	D25 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • Lens to be ordered individually (MX-B036 to MX-B237) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	1.580 g	16,0 cm		
	MX-D25-BOD1-N	4047438025256	30,5 cm	C	738,00 EUR
	D25 Body 6MP, Night	85258091	23,5 cm		
	D25 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • Lens to be ordered individually (MX-B036 to MX-B237) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	1.580 g	16,0 cm		
	MX-D25M-Sec-D23-F1.8	4047438021586	30,5 cm	C	748,00 EUR
	D25 5MP, L23-F1.8 (Day)	85258091	23,5 cm		
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L23 (f/1.8) super wide-angle (horizontal image angle 92°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX -232-IO-Box, audio via ExtIO	1.580 g	16,0 cm		
	MX-D25M-Sec-D25-F1.8	4047438021777	30,5 cm	C	748,00 EUR
	D25 5MP, L25-F1.8 (Day)	85258091	23,5 cm		
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L25 (f/1.8) super wide-angle (horizontal image angle 82°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX -232-IO-Box, audio via ExtIO	1.580 g	16,0 cm		
	MX-D25M-Sec-D38-F1.8	4047438021593	30,5 cm	C	748,00 EUR
	D25 5MP, L38-F1.8 (Day)	85258091	23,5 cm		
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L38 (f/1.8) wide-angle (horizontal image angle 55°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX -232-IO-Box, audio via ExtIO	1.580 g	16,0 cm		
	MX-D25M-Sec-D51-F1.8	4047438021609	30,5 cm	C	748,00 EUR
	D25 5MP, L51-F1.8 (Day)	85258091	23,5 cm		
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L51 (f/1.8) wide-angle (horizontal image angle 40°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX -232-IO-Box, audio via ExtIO	1.580 g	16,0 cm		

	MX-D25M-Sec-D76-F1.8	4047438021616	30,5 cm	C	748,00	EUR
	D25 5MP, L76-F1.8 (Day)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L76 (f/1.8) telephoto (horizontal image angle 27°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122° F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX -232-IO-Box, audio via ExtIO	1.580 g	16,0 cm			
	MX-D25M-Sec-D160-F1.8	4047438021623	30,5 cm	C	748,00	EUR
	D25 5MP, L160-F1.8 (Day)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L160 (f/1.8) telephoto (horizontal image angle 13°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122° F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX -232-IO-Box, audio via ExtIO	1.580 g	16,0 cm			
	MX-D25M-Sec	4047438019002	30,5 cm	C	688,00	EUR
	D25 5MP Body (Day)	85258091	23,5 cm			
	IP camera module with image sensor (body), lens to be ordered individually • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens options: L23 to L160 • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122° F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX-232-IO-Box, audio via ExtIO	1.580 g	16,0 cm			
	MX-D25M-Sec-Night-N23-F1.8	4047438021630	30,5 cm	C	748,00	EUR
	D25 5MP, L23-F1.8 (Night)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L23 (f/1.8) super wide-angle (horizontal image angle 92°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122° F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX -232-IO-Box, audio via ExtIO	1.580 g	16,0 cm			
	MX-D25M-Sec-Night-N25-F1.8	4047438021784	30,5 cm	C	748,00	EUR
	D25 5MP, L25-F1.8 (Night)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L25 (f/1.8) super wide-angle (horizontal image angle 82°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122° F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX -232-IO-Box, audio via ExtIO	1.580 g	16,0 cm			
	MX-D25M-Sec-Night-N38-F1.8	4047438021647	30,5 cm	C	748,00	EUR
	D25 5MP, L38-F1.8 (Night)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L38 (f/1.8) wide-angle (horizontal image angle 55°) • Max. image size: 5 MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122° F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX -232-IO-Box, audio via ExtIO	1.580 g	16,0 cm			
	MX-D25M-Sec-Night-N51-F1.8	4047438021654	30,5 cm	C	748,00	EUR
	D25 5MP, L51-F1.8 (Night)	85258091	23,5 cm			
	IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L51 (f/1.8) wide-angle (horizontal image angle 40°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122° F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX -232-IO-Box, audio via ExtIO	1.580 g	16,0 cm			

**MX-D25M-Sec-Night-N76-F1.8****D25 5MP, L76-F1.8 (Night)**

IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L76 (f/1.8) telephoto (horizontal image angle 27°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122° F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX-232-IO-Box, audio via ExtIO

4047438021661	30,5 cm	C	748,00	EUR
85258091	23,5 cm			
1.580 g	16,0 cm			

**MX-D25M-Sec-Night-N160-F1.8****D25 5MP, L160-F1.8 (Night)**

IP camera with image sensor and lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L160 (f/1.8) telephoto (horizontal image angle 13°) • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122° F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX-232-IO-Box, audio via ExtIO

4047438021678	30,5 cm	C	748,00	EUR
85258091	23,5 cm			
1.580 g	16,0 cm			

**MX-D25M-Sec-Night****D25 5MP Body (Night)**

IP camera module with image sensor (body), lens to be ordered individually • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens options: L23 to L160 • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122° F) • Internal DVR: 4 GB MicroSD • System components: Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.65 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via additional MX-232-IO-Box, audio via ExtIO

4047438019064	30,5 cm	C	688,00	EUR
85258091	23,5 cm			
1.580 g	16,0 cm			

D25 Dome Camera (SUP)

Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. These products can also be ordered from the standard program as individual components for self-assembly.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-D25-D036	4047438025126	30,5 cm	C	828,00 EUR
	D25 Complete Cam 6MP, 3.6 mm, Day	85258091	23,5 cm		
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	1.580 g	16,0 cm		
	MX-D25-D041	4047438025133	30,5 cm	C	828,00 EUR
	D25 Complete Cam 6MP, 4.1 mm, Day	85258091	23,5 cm		
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • Super wide lens B041 (f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	1.580 g	16,0 cm		
	MX-D25-D061	4047438025140	30,5 cm	C	828,00 EUR
	D25 Complete Cam 6MP, 6.1 mm, Day	85258091	23,5 cm		
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • Wide lens B061 (f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	1.580 g	16,0 cm		
	MX-D25-D079	4047438025157	30,5 cm	C	828,00 EUR
	D25 Complete Cam 6MP, 7.9 mm, Day	85258091	23,5 cm		
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • Standard lens B079 (f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	1.580 g	16,0 cm		
	MX-D25-D119	4047438025164	30,5 cm	C	828,00 EUR
	D25 Complete Cam 6MP, 11.9 mm, Day	85258091	23,5 cm		
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • Tele lens B119 (f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	1.580 g	16,0 cm		
	MX-D25-D237	4047438025171	30,5 cm	C	828,00 EUR
	D25 Complete Cam 6MP, 23.7 mm, Day	85258091	23,5 cm		
	IP camera with 6 Megapixel Moonlight Sensor, color (day) • Distance tele lens B237 (f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	1.580 g	16,0 cm		
	MX-D25-N036	4047438025188	30,5 cm	C	828,00 EUR
	D25 Complete Cam 6MP, 3.6 mm, Night	85258091	23,5 cm		
	IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	1.580 g	16,0 cm		

	MX-D25-N041 D25 Complete Cam 6MP, 4.1 mm, Night IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Super wide lens B041 (f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	4047438025195 85258091 1.580 g	30,5 cm 23,5 cm 16,0 cm	C	828,00 EUR
	MX-D25-N061 D25 Complete Cam 6MP, 6.1 mm, Night IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Wide lens B061 (f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	4047438025201 85258091 1.580 g	30,5 cm 23,5 cm 16,0 cm	C	828,00 EUR
	MX-D25-N079 D25 Complete Cam 6MP, 7.9 mm, Night IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Standard lens B079 (f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	4047438025218 85258091 1.580 g	30,5 cm 23,5 cm 16,0 cm	C	828,00 EUR
	MX-D25-N119 D25 Complete Cam 6MP, 11.9 mm, Night IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Tele lens B119 (f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	4047438025225 85258091 1.580 g	30,5 cm 23,5 cm 16,0 cm	C	828,00 EUR
	MX-D25-N237 D25 Complete Cam 6MP, 23.7 mm, Night IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Distance tele lens B237 (f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)	4047438025232 85258091 1.580 g	30,5 cm 23,5 cm 16,0 cm	C	828,00 EUR

V15 Vandalism Camera

High-Security Camera System

The V15 is the most sturdy MOBOTIX camera to-date. Specifically designed for high-risk areas, it offers unmatched protection against attacks. Nonetheless, it's still a camera with MOBOTIX technology and the full array of possibilities to connect external sensors and actuators. Constructed from 5 mm/0.2 in. stainless steel, the V15 is a bullet-resistant corner-mounted IP dual-lens camera designed for monitoring potentially volatile conditions. Made for high-security locations such as military sites, prisons and embassies or extreme environmental conditions.

Please note: V15 models will be finally fixed in Germany after receipt of your order. They are available with regular lead times up to 12 weeks.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP	
	MX-V15M-Sec-D22-6MP-F1.8	4047438024310	26,0 cm	C	2.498,00	EUR
	V15 Complete Cam 6MP, L22-F1.8 Lens, Day	85258091	26,0 cm			
	V15 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens L22/B041 (f/1.8, horiz. image angle 90°) • 3-5 mm stainless steel casing • IK10+ • HD Audio: Microphone and speaker integrated in the housing	4.680 g	26,0 cm			
	MX-V15D-Sec-D22D22-6MP-F1.8	4047438024334	26,0 cm	C	2.698,00	EUR
	V15 Complete Cam 2x 6MP, 2x L22-F1.8, Day	85258091	26,0 cm			
	V15 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x color (day), two HD premium lenses L22/B041 (f/1.8, horiz. image angle 90°) • 3-5 mm stainless steel casing • IK10+ • HD Audio: Microphone and speaker integrated in the housing	4.680 g	26,0 cm			
	MX-V15D-Sec-DNight-D22N22-6MP-F1.8	4047438024372	26,0 cm	C	2.698,00	EUR
	V15 Complete Cam 2x 6MP, 2x L22-F1.8, Day & Night	85258091	26,0 cm			
	V15 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses L22/B041 (f/1.8, horiz. image angle 90°) • 3-5 mm stainless steel casing • IK10+ • HD Audio: Microphone and speaker integrated in the housing	4.680 g	26,0 cm			
	MX-V15D-Sec-Night-N22N22-6MP-F1.8	4047438024358	26,0 cm	C	2.698,00	EUR
	V15 Complete Cam 2x 6MP, 2x L22-F1.8, Night	85258091	26,0 cm			
	V15 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses L22/B041 (f/1.8, horiz. image angle 90°) • 3-5 mm stainless steel casing • IK10+ • HD Audio: Microphone and speaker integrated in the housing	4.680 g	26,0 cm			
	MX-V15M-Sec-D43-6MP-F1.8	4047438024327	26,0 cm	C	2.498,00	EUR
	V15 Complete Cam 6MP, L43-F1.8 Lens, Day	85258091	26,0 cm			
	V15 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens L43/B079 (f/1.8, horiz. image angle 45°) • 3-5 mm stainless steel casing • IK10+ • HD Audio: Microphone and speaker integrated in the housing	4.680 g	26,0 cm			
	MX-V15D-Sec-D43D43-6MP-F1.8	4047438024341	26,0 cm	C	2.698,00	EUR
	V15 Complete Cam 2x 6MP, 2x L43-F1.8, Day	85258091	26,0 cm			
	V15 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x color (day), two HD premium lenses L43/B079 (f/1.8, horiz. image angle 45°) • 3-5 mm stainless steel casing • IK10+ • HD Audio: Microphone and speaker integrated in the housing	4.680 g	26,0 cm			

**MX-V15D-Sec-DNight-D43N43-6MP-F1.8****V15 Complete Cam 2x 6MP, 2x L43-F1.8, Day & Night**

V15 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses L43/B079 (f/1.8, horiz. image angle 45°) • 3-5 mm stainless steel casing • IK10++/IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing

4047438024389	26,0 cm	C	2.698,00	EUR
85258091	26,0 cm			
4.680 g	26,0 cm			

**MX-V15D-Sec-Night-N43N43-6MP-F1.8****V15 Complete Cam 2x 6MP, 2x L43-F1.8, Night**

V15D Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses L43/B079 (f/1.8, horiz. image angle 45°) • 3-5 mm stainless steel casing • IK10++/IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing

4047438024365	26,0 cm	C	2.698,00	EUR
85258091	26,0 cm			
4.680 g	26,0 cm			



Professional Video Systems Indoor

All prices are Manufacturer's suggested retail prices, net, ex works. Information subject to change without notice.
HS = Harmonized System Code DG = Discount Group

c25 Indoor Camera

Indoor Ceiling Camera. Easy To Install.

With a diameter of only 12 centimeters and a weight of approximately 200 grams, the c25 is the smallest and lightest hemispheric MOBOTIX video complete system for fast ceiling mounting in protected indoor areas. Features include a light-sensitive 6MP day or night sensor and MxAnalytics. Features all functions like the traditional Q25 outdoor camera.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-c25-D016	4047438026611	16,0 cm	C	428,00 EUR
	c25 Complete Cam 6MP, 1.6 mm, Day	85258091	13,0 cm		
	Hemispheric IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	400 g	13,0 cm		
	MX-c25-D036	4047438026635	16,0 cm	C	428,00 EUR
	c25 Complete Cam 6MP, 3.6 mm, Day	85258091	13,0 cm		
	IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	400 g	13,0 cm		
	MX-c25-N016	4047438026628	16,0 cm	C	428,00 EUR
	c25 Complete Cam 6MP, 1.6 mm, Night	85258091	13,0 cm		
	Hemispheric IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	400 g	13,0 cm		
	MX-c25-D016-AUD	4047438026659	16,0 cm	C	498,00 EUR
	c25 Complete Cam 6MP, 1.6 mm, Day, Audio Package	85258091	13,0 cm		
	Hemispheric IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	400 g	13,0 cm		
	MX-c25-D12-PW	4047438024273	16,0 cm	C	348,00 EUR
	c25 5MP, L12 (Day)	85258091	13,0 cm		
	Hemispheric IP indoor camera for ceiling mounting • Image sensor: 1/2.5" CMOS, 5 megapixel, color (day) • HD fisheye lens: L12 Hemispheric (f/2.0, horizontal image angle of 180°) • Max. image size: 5 MP (2592 x 1944 pixels) • IP20, 0 to 40 °C (32 to 104 °F) • Internal DVR: 4-GB MicroSD • Integrated microphone • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5-m Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB • Color: white	400 g	13,0 cm		
	MX-c25-D23-PW-F1.8	4047438025904	16,0 cm	C	348,00 EUR
	c25 5MP, L23-F1.8 (Day)	85258091	13,0 cm		
	IP indoor camera for ceiling mounting • Image sensor: 1/2.5" CMOS, 5 megapixel, color (day) • Premium lens: L23 super wide-angle lens (f/1.8, horiz. image angle 92°) • Maximum image size: 5 MP (2592 x 1944 Pixel) • IP20, 0°C to 40°C • 4 GB microSD • Integrated microphone • Temperature sensor, illumination sensor, shock detector, MxActivitySensor, MxAnalytics • 0.5-m Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB • Color: white	400 g	13,0 cm		

**MX-c25-N12-PW****c25 5MP, L12 (Night)**

Hemispheric IP indoor camera for ceiling mounting • Image sensor: 1/2.5" CMOS, 5 megapixel, black/white (night) • HD fisheye lens: L12 Hemispheric (f/2.0, horizontal image angle of 180°) • Max. image size: 5 MP • (2592 x 1944 pixels) • IP20, 0 to 40 °C (32 to 104 °F) • Internal DVR: 4-GB microSD • Integrated microphone • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5-m Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB • Color: white

4047438024280	16,0 cm	C	348,00	EUR
85258091	13,0 cm			
400 g	13,0 cm			

**MX-c25-N23-PW-F1.8****c25 5MP, L23-F1.8 (Night)**

IP indoor camera for ceiling mounting • Image sensor: 1/2.5" CMOS, 5 megapixel, black/white (night) • HD premium lens: L23 super wide-angle lens (f/1.8, horiz. image angle 92°) • Maximum image size: 5 MP (2592 x 1944 Pixel) • IP20, 0°C to 40°C • 4 GB microSD • Integrated microphone • Temperature sensor, illumination sensor, shock detector, MxActivitySensor, MxAnalytics • 0.5-m Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB • Color: white

4047438025911	16,0 cm	C	348,00	EUR
85258091	13,0 cm			
400 g	13,0 cm			

c25 Indoor Camera (SUP)

Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-c25-N036	4047438026642	16,0 cm	C	458,00 EUR
	c25 Complete Cam 6MP, 3.6 mm, Night	85258091	13,0 cm		
	IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	400 g	13,0 cm		
	MX-c25-D036-AUD	4047438026673	16,0 cm	C	528,00 EUR
	c25 Complete Cam 6MP, 3.6 mm, Day, Audio Package	85258091	13,0 cm		
	IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	400 g	13,0 cm		
	MX-c25-N016-AUD	4047438026666	16,0 cm	C	528,00 EUR
	c25 Complete Cam 6MP, 1.6 mm, Night, Audio Package	85258091	13,0 cm		
	Hemispheric IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	400 g	13,0 cm		
	MX-c25-N036-AUD	4047438026680	16,0 cm	C	528,00 EUR
	c25 Complete Cam 6MP, 3.6 mm, Night, Audio Package	85258091	13,0 cm		
	IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	400 g	13,0 cm		

i25 Indoor Camera

Perfect Wall Mount. Compact and Discrete.

The i25 is a 6MP hemispheric camera and is perfectly suited to be wall mounted with a tilt angle of 15 degree to achieve the best panoramic overview of a room without any blind spots. One i25 captures an entire room, easily replacing four standard CCTV cameras. The compact wall mount form factor fits into every environment.

The i25 can be wall mounted onto any surface. The small form factor matches perfectly with any environment. For fast installations, simply use the optional cavity installation set. A surface mount kit for concrete walls, for example, is available as well.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-i25-D016	4047438026697	16,0 cm	C	428,00 EUR
	i25 Complete Cam 6MP, 1.6 mm, Day	85258091	13,0 cm		
	Hemispheric IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	420 g	13,0 cm		
	MX-i25-D036	4047438026710	16,0 cm	C	428,00 EUR
	i25 Complete Cam 6MP, 3.6 mm, Day	85258091	13,0 cm		
	IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	420 g	13,0 cm		
	MX-i25-D016-AUD	4047438026734	16,0 cm	C	498,00 EUR
	i25 Complete Cam 6MP, 1.6 mm, Day, Audio Package	85258091	13,0 cm		
	Hemispheric IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	420 g	13,0 cm		
	MX-i25-D12-PW	4047438022019	16,0 cm	C	348,00 EUR
	i25 5MP, L12 (Day)	85258091	13,0 cm		
	Hemispheric IP indoor wall camera • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • HD fisheye lens: L12 hemispheric (horizontal image angle 180°) • Max. image size: 5MP (2592 x 1944 pixels) • IP30, 0 to 40°C (32 to 102°F) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, shock detector, MxActivitySensor, MxAnalytics • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB • Color: white	420 g	13,0 cm		
	MX-i25-D23-PW-F1.8	4047438022316	16,0 cm	C	348,00 EUR
	i25 5MP, L23-F1.8 (Day)	85258091	13,0 cm		
	IP indoor camera i25 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • HD lens: L23 super wide-angle (f/1.8, horizontal image angle of 92°) • Maximum image size: 5MP (2592 x 1944 pixels) • IP30, 0 °C to 40 °C (32 °F to 104 °F) • 4 GB microSD • Integrated microphone, temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5-m Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB • Color: white	420 g	13,0 cm		
	MX-i25-N12-PW	4047438022026	16,0 cm	C	348,00 EUR
	IP 5MP, L12 (Night)	85258091	13,0 cm		
	Hemispheric IP indoor wall camera • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • HD fisheye lens: L12 hemispheric (horizontal image angle 180°) • Max. image size: 5MP (2592 x 1944 pixels) • IP30, 0 to 40°C (32 to 102°F) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, shock detector, MxActivitySensor, MxAnalytics • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB • Color: white	420 g	13,0 cm		

**MX-i25-N23-PW-F1.8****i25 5MP, L23-F1.8 (Night)**

IP indoor camera i25 • Image sensor: 1/2.5" CMOS, 5 megapixels, black/white (night) • HD lens: L23 super wide-angle (f/1.8, horizontal image angle of 92°) • Maximum image size: 5MP (2592 1944 pixels) • IP30, 0 °C to 40 °C (32 °F to 104 °F) • 4 GB microSD • Integrated microphone, temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5-m Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB • Color: white

4047438022323	16,0 cm	C	348,00	EUR
85258091	13,0 cm			
420 g	13,0 cm			

i25 Indoor Camera (SUP)

Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-i25-N016	4047438026703	16,0 cm	C	458,00 EUR
	i25 Complete Cam 6MP, 1.6 mm, Night	85258091	13,0 cm		
		420 g	13,0 cm		
	Hemispheric IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white				
	MX-i25-N036	4047438026727	16,0 cm	C	458,00 EUR
	i25 Complete Cam 6MP, 3.6 mm, Night	85258091	13,0 cm		
		420 g	13,0 cm		
	IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white				
	MX-i25-D036-AUD	4047438026758	16,0 cm	C	528,00 EUR
	i25 Complete Cam 6MP, 3.6 mm, Day, Audio Package	85258091	13,0 cm		
		420 g	13,0 cm		
	IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Audio package with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white				
	MX-i25-N016-AUD	4047438026741	16,0 cm	C	528,00 EUR
	i25 Complete Cam 6MP, 1.6 mm, Night, Audio Package	85258091	13,0 cm		
		420 g	13,0 cm		
	Hemispheric IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white				
	MX-i25-N036-AUD	4047438026765	16,0 cm	C	528,00 EUR
	i25 Complete Cam 6MP, 3.6 mm, Night, Audio Package	85258091	13,0 cm		
		420 g	13,0 cm		
	IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Audio package with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white				

p25 Indoor Camera

The Flexible Ceiling Camera.

The p25 is a ceiling camera with a manual pan/tilt functionality providing full installation flexibility. Equipped with a telephoto lens, the p25 can be directed to a specific spot in the room. With a super wide lens and mounted in the corner, the p25 covers the entire space in 6MP resolution. A hemispheric version and on-wall kit is available, too. Beside the pre-built models, nearly all lens options can be self-assembled with a p25 day or night body.

The p25 is positioned extremely price competitive and represents with all included MOBOTIX features and the MOBOTIX video management system MxMC, one of the most attractive security solutions in the market.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-p25-D016	4047438026406	16,0 cm	C	448,00 EUR
	p25 Complete Cam 6MP, 1.6 mm, Day	85258091	13,0 cm		
	Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	480 g	13,0 cm		
	MX-p25-D036	4047438026420	16,0 cm	C	448,00 EUR
	p25 Complete Cam 6MP, 3.6 mm, Day	85258091	13,0 cm		
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	480 g	13,0 cm		
	MX-p25-BOD1	4047438026482	16,0 cm	C	388,00 EUR
	p25 Body 6MP, Day	85258091	13,0 cm		
	p25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (MX-B036 to MX-B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	480 g	13,0 cm		
	MX-p25-BOD1-N	4047438026499	16,0 cm	C	388,00 EUR
	p25 Body 6MP, Night	85258091	13,0 cm		
	p25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (MX-B036 to MX-B235, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	480 g	13,0 cm		
	MX-p25-D016-AUD	4047438026772	16,0 cm	C	498,00 EUR
	p25 Complete Cam 6MP, 1.6 mm, Day, Audio Package	85258091	13,0 cm		
	Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	480 g	13,0 cm		
	MX-p25-BOD1-AUD	4047438026819	16,0 cm	C	438,00 EUR
	p25 Body 6MP, Day, Audio Package	85258091	13,0 cm		
	p25 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (MX-B036 to MX-B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD-Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	480 g	13,0 cm		

**MX-p25-BOD1-N-AUD****p25 Body 6MP, Night, Audio Package**

p25 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • Lens to be ordered individually (MX-B036 to MX-B235, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

4047438026826	16,0 cm	C	438,00	EUR
85258091	13,0 cm			
480 g	13,0 cm			

p25 Indoor Camera (SUP)

Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. Many products of the supplemental program can be ordered from the standard program as individual components for self-assembly.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-p25-D061	4047438026444	16,0 cm	C	478,00 EUR
	p25 Complete Cam 6MP, 6.1 mm, Day	85258091	13,0 cm		
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Wide lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	480 g	13,0 cm		
	MX-p25-D079	4047438026451	16,0 cm	C	478,00 EUR
	p25 Complete Cam 6MP, 7.9 mm, Day	85258091	13,0 cm		
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Standard lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	480 g	13,0 cm		
	MX-p25-D119	4047438026468	16,0 cm	C	478,00 EUR
	p25 Complete Cam 6MP, 11.9 mm, Day	85258091	13,0 cm		
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Tele lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	480 g	13,0 cm		
	MX-p25-D237	4047438026475	16,0 cm	C	478,00 EUR
	p25 Complete Cam 6MP, 23.7 mm, Day	85258091	13,0 cm		
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Distant Tele lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	480 g	13,0 cm		
	MX-p25-N016	4047438026413	16,0 cm	C	478,00 EUR
	p25 Complete Cam 6MP, 1.6 mm, Night	85258091	13,0 cm		
	Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	480 g	13,0 cm		
	MX-p25-N036	4047438026437	16,0 cm	C	478,00 EUR
	p25 Complete Cam 6MP, 3.6 mm, Night	85258091	13,0 cm		
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra Wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white	480 g	13,0 cm		

**MX-p25-D036-AUD****p25 Complete Cam 6MP, 3.6 mm, Day, Audio Package**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

4047438026796	16,0 cm	C	528,00	EUR
85258091	13,0 cm			
480 g	13,0 cm			

**MX-p25-N016-AUD****p25 Complete Cam 6MP, 1.6 mm, Night, Audio Package**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

4047438026789	16,0 cm	C	528,00	EUR
85258091	13,0 cm			
480 g	13,0 cm			

**MX-p25-N036-AUD****p25 Complete Cam 6MP, 3.6 mm, Night, Audio Package**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

4047438026802	16,0 cm	C	528,00	EUR
85258091	13,0 cm			
480 g	13,0 cm			

v25 Indoor Dome Camera

Perfect Protection. Professional Functions.

The v25 offers as 6MP indoor dome camera all outstanding MOBOTIX features. In addition to the standard lens options there is also an optional on-wall audio kit and optional vandalism sets with stainless steel housing ring and reinforced lens cover for perfect protection.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-v25-BOD1	4047438027571	20,5 cm	C	388,00 EUR
	v25 Body 6MP, Day, White	85258091	20,0 cm		
	v25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (MX-B036 to MX-B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Housing color: white	690 g	12,5 cm		
	MX-v25-BOD1-b	4047438027656	20,5 cm	C	388,00 EUR
	v25 Body 6MP, Day, Black	85258091	20,0 cm		
	v25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (MX-B036 to MX-B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Housing color: black	690 g	12,5 cm		
	MX-v25-BOD1-N	4047438027588	20,5 cm	C	388,00 EUR
	v25 Body 6MP, Night, White	85258091	20,0 cm		
	v25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (MX-B036 to MX-B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Housing color: white	690 g	12,5 cm		
	MX-v25-BOD1-N-b	4047438027663	20,5 cm	C	388,00 EUR
	v25 Body 6MP, Night, Black	85258091	20,0 cm		
	v25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (MX-B036 to MX-B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Housing color: black	690 g	12,5 cm		
	MX-v25-D036	4047438027649	20,5 cm	C	448,00 EUR
	v25 Complete Cam 6MP, Day, White	85258091	20,0 cm		
	IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle 0° to -90° • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Housing color: white	700 g	12,5 cm		



Professional Video Systems Thermal

All prices are Manufacturer's suggested retail prices, net, ex works. Information subject to change without notice.
HS = Harmonized System Code DG = Discount Group

M15 Thermal Camera

Thermal. Dual-Lens Camera. Detect And Identify.

The modular design of the M15 platform provides the ultimate in flexibility. The M15-Thermal is factory-fitted with a thermal image sensor for accurate movement detection over long distances in all lighting conditions. An additional (optional) image sensor is used to identify people and objects.

Thermal Radiometry (TR): The camera models with Thermal Radiometry (TR) are able to measure thermal radiation across the entire image area in order to trigger a camera alarm based on the temperature increasing above or decreasing below an individually set trigger level.

All thermal cameras will be finally fixed in Germany after receipt of your order. They are available with regular lead times up to 12 weeks.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-M15-TR079	4047438027014	34,5 cm	B	4.628,00 EUR
	M15 Thermographic Camera TR, 50 mK, B079 (45°)	85258091	34,0 cm		
	IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/32° • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 344 x 256 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker (microphone via optional 6MP sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box	2.480 g	20,0 cm		
	MX-M15-TR119	4047438027021	34,5 cm	B	4.498,00 EUR
	M15 Thermographic Camera TR, 50 mK, B119 (25°)	85258091	34,0 cm		
	IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 344 x 256 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker (microphone via optional 6MP sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box	2.480 g	20,0 cm		
	MX-M15-TR237	4047438027038	34,5 cm	B	4.498,00 EUR
	M15 Thermographic Camera TR, 50 mK, B237 (17°)	85258091	34,0 cm		
	IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 344 x 256 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker (microphone via optional 6MP sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box	2.480 g	20,0 cm		
	MX-M15D-Thermal-L43	4047438020589	34,5 cm	B	4.128,00 EUR
	M15 Thermographic Camera, 50 mK, L43 (45°)	85258091	34,0 cm		
	IP thermographic camera with L43 thermal lens, horizontal/vertical image angle 45°/32°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker (microphone via sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box	2.460 g	20,0 cm		

**MX-M15D-Thermal-L65****M15 Thermographic Camera, 50 mK, L65 (25°)**

IP thermographic camera with L65 thermal lens, horizontal/vertical image angle 25°/19°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker (microphone via sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box

4047438020596	34,5 cm	B	3.998,00	EUR
85258091	34,0 cm			
2.460 g	20,0 cm			

**MX-M15D-Thermal-L135****M15 Thermographic Camera, 50 mK, L135 (17°)**

IP thermographic camera with L135 thermal lens, horizontal/vertical image angle 17°/13°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • System components: speaker (microphone via sensor module), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box

4047438020602	34,5 cm	B	3.998,00	EUR
85258091	34,0 cm			
2.460 g	20,0 cm			

S15 Thermal Camera Modules

For The World's First Flexible Dual Thermal Camera.

These thermal sensor modules are also designed for connection to the S15 camera (body), for example, for customer-specific special installations. Here, it is possible to connect two thermal sensor modules to a S15 Body in a very flexible way using max. 3 meter long cables for each module. MOBOTIX thermal cameras are designed for around-the-clock operation in industrial conditions. Just like for the M15-Thermal, there are different horizontal image angles available: 45°, 25° and 17° (with optional TR technology for temperature measurement).

Please note: These models will be finally fixed in Germany after receipt of your order. They are available with regular lead times up to 12 weeks.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP	
	MX-SM-TR079	4047438027090	16,0 cm	B	3.598,00	EUR
	Thermal Sensor Module TR For S15, 50 mK, B079 (45°)	90275000	13,0 cm			
	Thermal Sensor Module TR for the S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 256 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,0 cm			
	MX-SM-TR119	4047438027106	16,0 cm	B	3.468,00	EUR
	Thermal Sensor Module TR For S15, 50 mK, B119 (25°)	90275000	13,0 cm			
	Thermal Sensor Module TR for the S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 256 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,0 cm			
	MX-SM-TR237	4047438027113	16,0 cm	B	3.468,00	EUR
	Thermal Sensor Module TR For S15, 50 mK, B237 (17°)	90275000	13,0 cm			
	Thermal Sensor Module TR for the S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 256 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,0 cm			
	MX-MT-PT-TR079	4047438027045	17,5 cm	B	3.728,00	EUR
	PTMount-Thermal TR For S15, 50 mK, B079 (45°), White	90275000	13,5 cm			
	PTMount-Thermal TR for the S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 256 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	890 g	14,0 cm			
	MX-MT-PT-TR119	4047438027052	17,5 cm	B	3.598,00	EUR
	PTMount-Thermal TR For S15, 50 mK, B119 (25°), White	90275000	13,5 cm			
	PTMount-Thermal TR for the S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 256 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	890 g	14,0 cm			
	MX-MT-PT-TR237	4047438027069	17,5 cm	B	3.598,00	EUR
	PTMount-Thermal TR For S15, 50 mK, B237 (17°), White	90275000	13,5 cm			
	PTMount-Thermal TR for the S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 256 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	890 g	14,0 cm			

	MX-MT-PT-TR079-b	4047438027120	17,5 cm	B	3.728,00	EUR
	PTMount-Thermal TR For S15, 50 mK, B079 (45°), Black	90275000	13,5 cm			
	PTMount-Thermal TR for the S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 256 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black	890 g	14,0 cm			
	MX-MT-PT-TR119-b	4047438027137	17,5 cm	B	3.598,00	EUR
	PTMount-Thermal TR For S15, 50 mK, B119 (25°), Black	90275000	13,5 cm			
	PTMount-Thermal TR for the S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 256 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black	890 g	14,0 cm			
	MX-MT-PT-TR237-b	4047438027144	17,5 cm	B	3.598,00	EUR
	PTMount-Thermal TR For S15, 50 mK, B237 (17°), Black	90275000	13,5 cm			
	PTMount-Thermal TR for the S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 256 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black	890 g	14,0 cm			
	MX-SM-Thermal-L43	4047438018265	16,0 cm	B	3.098,00	EUR
	Thermal Sensor Module For S15, 50 mK, L43 (45°)	90275000	13,0 cm			
	Suitable for: S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): L43, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	535 g	13,0 cm			
	MX-SM-Thermal-L65	4047438018272	16,0 cm	B	2.968,00	EUR
	Thermal Sensor Module For S15, 50 mK, L65 (25°)	90275000	13,0 cm			
	Suitable for: S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): L65, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	535 g	13,0 cm			
	MX-SM-Thermal-L135	4047438018289	16,0 cm	B	2.968,00	EUR
	Thermal Sensor Module For S15, 50 mK, L135 (17°)	90275000	13,0 cm			
	Suitable for: S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): L135, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	535 g	13,0 cm			
	MX-SM-PTMount-Thermal-L43-PW	4047438021883	17,5 cm	B	3.228,00	EUR
	PTMount-Thermal For S15, 50 mK, L43 (45°), White	90275000	13,5 cm			
	PTMount-Thermal with integrated highly sensitive thermal image sensor for the S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): L43, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	870 g	14,0 cm			

	MX-SM-PTMount-Thermal-L65-PW	4047438021890	17,5 cm	B	3.098,00	EUR
	PTMount-Thermal For S15, 50 mK, L65 (25°), White	90275000	13,5 cm			
	PTMount-Thermal with integrated highly sensitive thermal image sensor for the S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): L65, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	870 g	14,0 cm			
	MX-SM-PTMount-Thermal-L135-PW	4047438021906	17,5 cm	B	3.098,00	EUR
	PTMount Thermal For S15, 50 mK, L135 (17°), White	90275000	13,5 cm			
	PTMount-Thermal with integrated highly sensitive thermal image sensor for the S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): L135, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	870 g	14,0 cm			
	MX-SM-PTMount-Thermal-L43-BL	4047438026376	17,5 cm	B	3.228,00	EUR
	PTMount-Thermal For S15, 50 mK, L43 (45°), Black	90275000	13,5 cm			
	PTMount-Thermal with integrated highly sensitive thermal image sensor for the S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): L43, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black	870 g	14,0 cm			
	MX-SM-PTMount-Thermal-L65-BL	4047438026383	17,5 cm	B	3.098,00	EUR
	PTMount-Thermal For S15, 50 mK, L65 (25°), Black	90275000	13,5 cm			
	PTMount-Thermal with integrated highly sensitive thermal image sensor for the S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): L65, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black	870 g	14,0 cm			
	MX-SM-PTMount-Thermal-L135-BL	4047438026390	17,5 cm	B	3.098,00	EUR
	PTMount Thermal For S15, 50 mK, L135 (17°), Black	90275000	13,5 cm			
	PTMount-Thermal with integrated highly sensitive thermal image sensor for the S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): L65, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: black	870 g	14,0 cm			



Optics

All prices are Manufacturer's suggested retail prices, net, ex works. Information subject to change without notice.
HS = Harmonized System Code DG = Discount Group

Sensor Modules S15/M15 6MP

Flexible Optics. With 6MP Moonlight Sensor Technology.

The external part of the sensor module is available in white and black, which makes the camera nearly invisible in most installations (IP66). With integrated lens, image sensor and microphone, preassembled for ceiling or wall mounting. Easy connection to the housing via quick connector. Also available as LPF versions.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-SM-D10-PW-6MP	4047438022514	10,3 cm	C	198,00 EUR
	Sensor Module 6MP, L10-F2.0 (Day), White	90021900	6,5 cm		
	Sensor module S15/M15 with HD premium fisheye lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	10,3 cm		
	MX-SM-D20-PW-6MP-F1.8	4047438022521	10,3 cm	C	198,00 EUR
	Sensor Module 6MP, L20-F1.8 (Day), White	90021900	6,5 cm		
	Sensor module S15/M15 with HD premium lens L20/B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	10,3 cm		
	MX-SM-D22-PW-6MP-F1.8	4047438022538	10,3 cm	C	198,00 EUR
	Sensor Module 6MP, L22-F1.8 (Day), White	90021900	6,5 cm		
	Sensor module S15/M15 with HD premium lens L22/B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	10,3 cm		
	MX-SM-D32-PW-6MP-F1.8	4047438022545	10,3 cm	C	198,00 EUR
	Sensor Module 6MP, L32-F1.8 (Day), White	90021900	6,5 cm		
	Sensor module S15/M15 with HD premium lens L32/B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	10,3 cm		
	MX-SM-D43-PW-6MP-F1.8	4047438022552	10,3 cm	C	198,00 EUR
	Sensor Module 6MP, L43-F1.8 (Day), White	90021900	6,5 cm		
	Sensor module S15/M15 with HD premium lens L43/B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	10,3 cm		
	MX-SM-D65-PW-6MP-F1.8	4047438022569	10,3 cm	C	198,00 EUR
	Sensor Module 6MP, L65-F1.8 (Day), White	90021900	6,5 cm		
	Sensor module S15/M15 with HD premium lens L65/B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	10,3 cm		
	MX-SM-D135-PW-6MP-F1.8	4047438022576	10,3 cm	C	198,00 EUR
	Sensor Module 6MP, L135-F1.8 (Day), White	90021900	6,5 cm		
	Sensor module S15/M15 with HD premium lens L135/B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	144 g	10,3 cm		

	MX-SM-D270-PW-6MP Sensor Module 6MP, L270-F2.5 (Day), White Sensor module S15/M15 with HD premium lens L270/B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438022583 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-D045-100-CS Sensor Module 6MP, CSVario 4,5-10 mm, Day, White Sensor module S15/M15 with CSVario Lens B045-100-CS focal length 4.5-10 mm, f/1.6-2.3, 39°-89° x 29°-65° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white	4047438026918 90021900 190 g	8,5 cm 10,5 cm 5,0 cm	C	298,00 EUR
	MX-SM-D-CS Sensor Module 6MP, CS-Mount, Day, White Sensor module S15/M15 for standard lenses with CS mount (e.g., for Vario lens MX-B045-100-CS) • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white	4047438026857 90021900 146 g	8,5 cm 10,5 cm 5,0 cm	C	178,00 EUR
	MX-SM-N10-PW-6MP Sensor Module 6MP, L10-F2.0 (Night), White Sensor module S15/M15 with HD premium fisheye lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	4047438022590 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-N20-PW-6MP-F1.8 Sensor Module 6MP, L20-F1.8 (Night), White Sensor module S15/M15 with HD premium lens L20/B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	4047438022606 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-N22-PW-6MP-F1.8 Sensor Module 6MP, L22-F1.8 (Night), White Sensor module S15/M15 with HD premium lens L22/B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	4047438022613 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-N32-PW-6MP-F1.8 Sensor Module 6MP, L32-F1.8 (Night), White Sensor module S15/M15 with HD premium lens L32/B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	4047438022620 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-N43-PW-6MP-F1.8 Sensor Module 6MP, L43-F1.8 (Night), White Sensor module S15/M15 with HD premium lens L43/B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	4047438022637 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR

	MX-SM-N65-PW-6MP-F1.8 Sensor Module 6MP, L65-F1.8 (Night), White Sensor module S15/M15 with HD premium lens L65/B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	4047438022644 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-N135-PW-6MP-F1.8 Sensor Module 6MP, L135-F1.8 (Night), White Sensor module S15/M15 with HD premium lens L135/B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	4047438022651 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-N270-PW-6MP Sensor Module 6MP, L270-F2.5 (Night), White Sensor module S15/M15 with HD premium lens L270/B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white	4047438022668 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-N045-100-CS Sensor Module 6MP, CSVario 4,5-10 mm, Night, White Sensor module S15/M15 with CSVario Lens B045-100-CS (focal length 4.5-10 mm, f/1.6-2.3, 39°-89° x 29°-65°) • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white	4047438026925 90021900 190 g	8,5 cm 10,5 cm 5,0 cm	C	298,00 EUR
	MX-SM-N-CS Sensor Module 6MP, CS-Mount, Night, White Sensor module S15/M15 for standard lenses with CS mount (e.g., for Vario lens MX-B045-100-CS) • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white	4047438026864 90021900 146 g	8,5 cm 10,5 cm 5,0 cm	C	178,00 EUR
	MX-SM-N10-LPF-PW-6MP Sensor Module 6MP, L10-F2.0 (Night LPF), White Sensor module S15/M15 with HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white	4047438022675 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	298,00 EUR
	MX-SM-N20-LPF-PW-6MP-F1.8 Sensor Module 6MP, L20-F1.8 (Night LPF), White Sensor module S15/M15 with HD premium lens L20/B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white	4047438022682 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	298,00 EUR
	MX-SM-N22-LPF-PW-6MP-F1.8 Sensor Module 6MP, L22-F1.8 (Night LPF), White Sensor module S15/M15 with HD premium lens L22/B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white	4047438022699 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	298,00 EUR

	MX-SM-N32-LPF-PW-6MP-F1.8 Sensor Module 6MP, L32-F1.8 (Night LPF), White Sensor module S15/M15 with HD premium lens L32/B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white	4047438022705 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	298,00 EUR
	MX-SM-N43-LPF-PW-6MP-F1.8 Sensor Module 6MP, L43-F1.8 (Night LPF), White Sensor module S15/M15 with HD premium lens L43/B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white	4047438022712 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	298,00 EUR
	MX-SM-N65-LPF-PW-6MP-F1.8 Sensor Module 6MP, L65-F1.8 (Night LPF), White Sensor module S15/M15 with HD premium lens L65/B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white	4047438022729 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	298,00 EUR
	MX-SM-N135-LPF-PW-6MP-F1.8 Sensor Module 6MP, L135-F1.8 (Night LPF), White Sensor module S15/M15 with HD premium lens L135/B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white	4047438022736 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	298,00 EUR
	MX-SM-N270-LPF-PW-6MP Sensor Module 6MP, L270-F2.5 (Night LPF), White Sensor module S15/M15 with HD premium lens L270/B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white	4047438022743 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	298,00 EUR
	MX-SM-D10-BL-6MP Sensor Module 6MP, L10-F2.0 (Day), Black Sensor module S15/M15 with HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black	4047438022750 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-D20-BL-6MP-F1.8 Sensor Module 6MP, L20-F1.8 (Day), Black Sensor module S15/M15 with HD premium lens L20/B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black	4047438022767 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-D22-BL-6MP-F1.8 Sensor Module 6MP, L22-F1.8 (Day), Black Sensor module S15/M15 with HD premium lens L22/B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black	4047438022774 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR

	MX-SM-D32-BL-6MP-F1.8 Sensor Module 6MP, L32-F1.8 (Day), Black Sensor module S15/M15 with HD premium lens L32/B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black	4047438022781 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-D43-BL-6MP-F1.8 Sensor Module 6MP, L43-F1.8 (Day), Black Sensor module S15/M15 with HD premium lens L43/B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black	4047438022798 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-D65-BL-6MP-F1.8 Sensor Module 6MP, L65-F1.8 (Day), Black Sensor module S15/M15 with HD premium lens L65/B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black	4047438022804 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-D135-BL-6MP-F1.8 Sensor Module 6MP, L135-F1.8 (Day), Black Sensor module S15/M15 with HD premium lens L135/B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black	4047438022811 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-D270-BL-6MP Sensor Module 6MP, L270-F2.5 (Day), Black Sensor module S15/M15 with HD premium lens L270/B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black	4047438022828 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-N10-BL-6MP Sensor Module 6MP, L10-F2.0 (Night), Black Sensor module S15/M15 with HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438022835 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-N20-BL-6MP-F1.8 Sensor Module 6MP, L20-F1.8 (Night), Black Sensor module S15/M15 with HD premium lens L20/B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438022842 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-N22-BL-6MP-F1.8 Sensor Module 6MP, L22-F1.8 (Night), Black Sensor module S15/M15 with HD premium lens L22/B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438022859 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR

	MX-SM-N32-BL-6MP-F1.8 Sensor Module 6MP, L32-F1.8 (Night), Black Sensor module S15/M15 with HD premium lens L32/B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438022866 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-N43-BL-6MP-F1.8 Sensor Module 6MP, L43-F1.8 (Night), Black Sensor module S15/M15 with HD premium lens L43/B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438022873 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-N65-BL-6MP-F1.8 Sensor Module 6MP, L65-F1.8 (Night), Black Sensor module S15/M15 with HD premium lens L65/B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438022880 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-N135-BL-6MP-F1.8 Sensor Module 6MP, L135-F1.8 (Night), Black Sensor module S15/M15 with HD premium lens L135/B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438022897 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-N270-BL-6MP Sensor Module 6MP, L270-F2.5 (Night), Black Sensor module S15/M15 with HD premium lens L270/B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black	4047438022903 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	198,00 EUR
	MX-SM-N10-LPF-BL-6MP Sensor Module 6MP, L10-F2.0 (Night LPF), Black Sensor module S15/M15 with HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black	4047438022910 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	298,00 EUR
	MX-SM-N20-LPF-BL-6MP-F1.8 Sensor Module 6MP, L20-F1.8 (Night LPF), Black Sensor module S15/M15 with HD premium lens L20/B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black	4047438022927 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	298,00 EUR
	MX-SM-N22-LPF-BL-6MP-F1.8 Sensor Module 6MP, L22-F1.8 (Night LPF), Black Sensor module S15/M15 with HD premium lens L22/B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black	4047438022934 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	298,00 EUR

	MX-SM-N32-LPF-BL-6MP-F1.8 Sensor Module 6MP, L32-F1.8 (Night LPF), Black Sensor module S15/M15 with HD premium lens L32/B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black	4047438022941 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	298,00 EUR
	MX-SM-N43-LPF-BL-6MP-F1.8 Sensor Module 6MP, L43-F1.8 (Night LPF), Black Sensor module S15/M15 with HD premium lens L43/B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black	4047438022958 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	298,00 EUR
	MX-SM-N65-LPF-BL-6MP-F1.8 Sensor Module 6MP, L65-F1.8 (Night LPF), Black Sensor module S15/M15 with HD premium lens L65/B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black	4047438022965 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	298,00 EUR
	MX-SM-N135-LPF-BL-6MP-F1.8 Sensor Module 6MP, L135-F1.8 (Night LPF), Black Sensor module S15/M15 with HD premium lens L135/B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black	4047438022972 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	298,00 EUR
	MX-SM-N270-LPF-BL-6MP Sensor Module 6MP, L270-F2.5 (Night LPF), Black Sensor module S15/M15 with HD premium lens L270/B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black	4047438022989 90021900 144 g	10,3 cm 6,5 cm 10,3 cm	C	298,00 EUR

Sensor Modules S15/M15 5MP Premium

Flexible Optics. Fitted With 5MP Sensor.




The visible external part of the sensor module is available in white and black, enabling it to blend into most installation environments indoors and outdoors (IP66). With integrated lens, image sensor and microphone, preassembled for ceiling or wall mounting. Easy connection to the housing via quick connector. Also available as LPF version.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-SM-D23-PW-F1.8	4047438022415	10,3 cm	C	148,00 EUR
	Sensor Module 5MP, L23-F1.8 (Day), White	90021900	6,5 cm		
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • HD Premium lens L23 super wide-angle (f/1.8, horizontal image angle 92°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm		
	MX-SM-D25-PW-F1.8	4047438022217	10,3 cm	C	148,00 EUR
	Sensor Module 5MP, L25-F1.8 (Day), White	90021900	6,5 cm		
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • HD Premium lens L25 super wide-angle (f/1.8, horizontal image angle 82°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm		
	MX-SM-D38-PW-F1.8	4047438023580	10,3 cm	C	148,00 EUR
	Sensor Module 5MP, L38-F1.8 (Day), White	90021900	6,5 cm		
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • HD Premium lens L38 wide-angle (f/1.8, horizontal image angle 55°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm		
	MX-SM-D51-PW-F1.8	4047438023641	10,3 cm	C	148,00 EUR
	Sensor Module 5MP, L51-F1.8 (Day), White	90021900	6,5 cm		
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • HD Premium lens L51 wide-angle (f/1.8, horizontal image angle 40°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm		
	MX-SM-D76-PW-F1.8	4047438023702	10,3 cm	C	148,00 EUR
	Sensor Module 5MP, L76-F1.8 (Day), White	90021900	6,5 cm		
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • HD Premium lens L76 tele (f/1.8, horizontal image angle 27°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm		
	MX-SM-D160-PW-F1.8	4047438023764	10,3 cm	C	148,00 EUR
	Sensor Module 5MP, L160-F1.8 (Day), White	90021900	6,5 cm		
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L160 tele (f/1.8, horizontal image angle 13°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm		
	MX-SM-D320-PW	4047438021692	10,3 cm	C	148,00 EUR
	Sensor Module 5MP, L320 (Day), White	90021900	6,5 cm		
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Max. image size: 5MP (2592 x 1944 pixels) • Premium lens L320 super-tele (f/2.5, horizontal image angle 7°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm		

	MX-SM-N12-PW	4047438017794	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L12 (Night), White	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L12 Hemispheric (horizontal image angle 180°) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Integrated microphone and status LEDs • Transparent dome made of polycarbonate • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm			
	MX-SM-N23-PW-F1.8	4047438022422	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L23-F1.8 (Night), White	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • HD Premium lens L23 super wide-angle (f/1.8, horizontal image angle 92°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm			
	MX-SM-N25-PW-F1.8	4047438022224	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L25-F1.8 (Night), White	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • HD Premium lens L25 super wide-angle (f/1.8, horizontal image angle 82°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm			
	MX-SM-N38-PW-F1.8	4047438023597	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L38-F1.8 (Night), White	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L38 wide-angle (f/1.8, horizontal image angle 55°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm			
	MX-SM-N51-PW-F1.8	4047438023658	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L51-F1.8 (Night), White	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L51 wide-angle (f/1.8, horizontal image angle 40°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm			
	MX-SM-N76-PW-F1.8	4047438023719	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L76-F1.8 (Night), White	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L76 tele (f/1.8, horizontal image angle 27°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm			
	MX-SM-N160-PW-F1.8	4047438023771	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L160-F1.8 (Night), White	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L160 tele (f/1.8, horizontal image angle 13°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm			
	MX-SM-N320-PW	4047438021708	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L320 (Night), White	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • Premium lens L320 super-tele (f/2.5, horizontal image angle 7°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm			

	MX-SM-N12-LPF-PW	4047438019668	10,3 cm	C	248,00	EUR
	Sensor Module 5MP, Hemispheric L12 (Night LPF), White	90021900	6,5 cm			
	Suitable for: S15, M15 • LPF special optic: e.g. for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L12 Hemispheric (horizontal image angle 180°) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Integrated microphone and status LEDs • Transparent dome made of polycarbonate • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm			
	MX-SM-N23-LPF-PW-F1.8	4047438022439	10,3 cm	C	248,00	EUR
	Sensor Module 5MP, L23-F1.8 (Night LPF), White	90021900	6,5 cm			
	Suitable for: S15, M15 • LPF special optic: e.g. for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • HD Premium lens L23 super wide-angle (f/1.8, horizontal image angle 92°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm			
	MX-SM-N25-LPF-PW-F1.8	4047438022231	10,3 cm	C	248,00	EUR
	Sensor Module 5MP, L25-F1.8 (Night LPF), White	90021900	6,5 cm			
	Suitable for: S15, M15 • LPF special optic: e.g. for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • HD Premium lens L25 super wide-angle (f/1.8, horizontal image angle 82°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm			
	MX-SM-N38-LPF-PW-F1.8	4047438023603	10,3 cm	C	248,00	EUR
	Sensor Module 5MP, L38-F1.8 (Night LPF), White	90021900	6,5 cm			
	Suitable for: S15, M15 • LPF special optic: e.g. for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L38 wide-angle (f/1.8, horizontal image angle 55°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm			
	MX-SM-N51-LPF-PW-F1.8	4047438023665	10,3 cm	C	248,00	EUR
	Sensor Module 5MP, L51-F1.8 (Night LPF), White	90021900	6,5 cm			
	Suitable for: S15, M15 • LPF special optic: e.g. for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L51 wide-angle (f/1.8, horizontal image angle 40°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm			
	MX-SM-N76-LPF-PW-F1.8	4047438023726	10,3 cm	C	248,00	EUR
	Sensor Module 5MP, L76-F1.8 (Night LPF), White	90021900	6,5 cm			
	Suitable for: S15, M15 • LPF special optic: e.g. for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L76 tele (f/1.8, horizontal image angle 27°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm			
	MX-SM-N160-LPF-PW-F1.8	4047438023788	10,3 cm	C	248,00	EUR
	Sensor Module 5MP, L160-F1.8 (Night LPF), White	90021900	6,5 cm			
	Suitable for: S15, M15 • LPF special optic: e.g. for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L160 tele (f/1.8, horizontal image angle 13°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: white	144 g	10,3 cm			

	MX-SM-D12-BL	4047438017855	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L12 (Day), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L12 Hemispheric (horizontal image angle 180°) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Integrated microphone and status LEDs • Transparent dome made of polycarbonate • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-D23-BL-F1.8	4047438022446	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L23-F1.8 (Day), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • HD Premium lens L23 super wide-angle (f/1.8, horizontal image angle 92°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-D38-BL-F1.8	4047438023610	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L38-F1.8 (Day), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L38 wide-angle (f/1.8, horizontal image angle 55°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-D51-BL-F1.8	4047438023672	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L51-F1.8 (Day), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L51 wide-angle (f/1.8, horizontal image angle 40°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-D76-BL-F1.8	4047438023733	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L76-F1.8 (Day), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L76 tele (f/1.8, horizontal image angle 27°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-D160-BL-F1.8	4047438023795	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L160-F1.8 (Day), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L160 tele (f/1.8, horizontal image angle 13°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-D25-BL-F1.8	4047438022248	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L25-F1.8 (Day), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • HD Premium lens L25 super wide-angle (f/1.8, horizontal image angle 82°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-N12-BL	4047438017916	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L12 (Night), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L12 Hemispheric (horizontal image angle 180°) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Integrated microphone and status LEDs • Transparent dome made of polycarbonate • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			

	MX-SM-N23-BL-F1.8	4047438022453	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L23-F1.8 (Night), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, BW (night) • HD Premium lens L23 super wide-angle (f/1.8, horizontal image angle 92°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-N38-BL-F1.8	4047438023627	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L38-F1.8 (Night), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L38 wide-angle (f/1.8, horizontal image angle 55°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-N51-BL-F1.8	4047438023689	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L51-F1.8 (Night), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L51 wide-angle (f/1.8, horizontal image angle 40°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-N76-BL-F1.8	4047438023740	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L76-F1.8 (Night), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L76 tele (f/1.8, horizontal image angle 27°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-N160-BL-F1.8	4047438023801	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L160-F1.8 (Night), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L160 tele (f/1.8, horizontal image angle 13°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-N25-BL-F1.8	4047438022255	10,3 cm	C	148,00	EUR
	Sensor Module 5MP, L25-F1.8 (Night), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • HD Premium lens L25 super wide-angle (f/1.8, horizontal image angle 82°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-N12-LPF-BL	4047438019729	10,3 cm	C	248,00	EUR
	Sensor Module 5MP, Hemispheric L12 (Night LPF), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • LPF special optic: e.g. for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L12 Hemispheric (horizontal image angle 180°) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Integrated microphone and status LEDs • Transparent dome made of polycarbonate • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-N23-LPF-BL-F1.8	4047438022460	10,3 cm	C	248,00	EUR
	Sensor Module 5MP, L23-F1.8 (Night LPF), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • LPF special optic: e.g. for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • HD Premium lens L23 super wide-angle (f/1.8, horizontal image angle 92°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			

	MX-SM-N25-LPF-BL-F1.8	4047438022262	10,3 cm	C	248,00	EUR
	Sensor Module 5MP, L25-F1.8 (Night LPF), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • LPF special optic: e.g. for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • HD Premium lens L25 super wide-angle (f/1.8, horizontal image angle 82°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-N38-LPF-BL-F1.8	4047438023634	10,3 cm	C	248,00	EUR
	Sensor Module 5MP, L38-F1.8 (Night LPF), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • LPF special optic: e.g. for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L38 wide-angle (f/1.8, horizontal image angle 55°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-N51-LPF-BL-F1.8	4047438023696	10,3 cm	C	248,00	EUR
	Sensor Module 5MP, L51-F1.8 (Night LPF), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • LPF special optic: e.g. for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L51 wide-angle (f/1.8, horizontal image angle 40°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-N76-LPF-BL-F1.8	4047438023757	10,3 cm	C	248,00	EUR
	Sensor Module 5MP, L76-F1.8 (Night LPF), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • LPF special optic: e.g. for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L76 tele (f/1.8, horizontal image angle 27°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			
	MX-SM-N160-LPF-BL-F1.8	4047438023818	10,3 cm	C	248,00	EUR
	Sensor Module 5MP, L160-F1.8 (Night LPF), Black	90021900	6,5 cm			
	Suitable for: S15, M15 • LPF special optic: e.g. for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens L160 tele (f/1.8, horizontal image angle 13°) • IP66, -30 to 60°C (-22 to 140°F) • Non-reflective lens protection layer made of tempered glass • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually) • Color: black	144 g	10,3 cm			

BlockFlexMounts S15 6MP

For Individual Mounting Solutions. Based On The Latest MOBOTIX 6MP Technology.

One or two BlockFlexMount sensor modules are connected to the S15 with a sensor cable just like the standard sensor modules. Each BlockFlexMount contains a microphone and status LEDs. Protection class IP30 (protected against access with a tool). Ambient temperature range: 0°C to +50°C/32°F to 122°F. Also available as LPF and CS mount versions.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-BFM-MX-D10-6MP	4047438024426	10,5 cm	C	168,00 EUR
	BlockFlexMount 6MP, Incl. Hemispheric L10 (Day)	90021900	8,5 cm		
	Suitable for: S15 • HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm		
	MX-BFM-MX-D20-6MP-F1.8	4047438024433	10,5 cm	C	168,00 EUR
	BlockFlexMount 6MP, Incl. L20-F1.8 (Day)	90021900	8,5 cm		
	Suitable for: S15 • HD premium lens L20/B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm		
	MX-BFM-MX-D22-6MP-F1.8	4047438024440	10,5 cm	C	168,00 EUR
	BlockFlexMount 6MP, Incl. L22-F1.8 (Day)	90021900	8,5 cm		
	Suitable for: S15 • HD premium lens L22/B036 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm		
	MX-BFM-MX-D32-6MP-F1.8	4047438024457	10,5 cm	C	168,00 EUR
	BlockFlexMount 6MP, Incl. L32-F1.8 (Day)	90021900	8,5 cm		
	Suitable for: S15 • HD premium lens L32/B041 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm		
	MX-BFM-MX-D43-6MP-F1.8	4047438024464	10,5 cm	C	168,00 EUR
	BlockFlexMount 6MP, Incl. L43-F1.8 (Day)	90021900	8,5 cm		
	Suitable for: S15 • HD premium lens L43/B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm		
	MX-BFM-MX-D65-6MP-F1.8	4047438024471	10,5 cm	C	168,00 EUR
	BlockFlexMount 6MP, Incl. L65-F1.8 (Day)	90021900	8,5 cm		
	Suitable for: S15 • HD premium lens L65/B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm		
	MX-BFM-MX-D135-6MP-F1.8	4047438024488	10,5 cm	C	168,00 EUR
	BlockFlexMount 6MP, Incl. L135-F1.8 (Day)	90021900	8,5 cm		
	Suitable for: S15 • HD premium lens L135/B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm		

	MX-BFM-MX-D270-6MP BlockFlexMount 6MP, incl. L270 (Day) Suitable for: S15 • HD premium lens L270/B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024495 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	168,00 EUR
	MX-BFM-CS-D-6MP BlockFlexMount 6MP, For CS Mount Lens (Day) Suitable for: S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024396 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	148,00 EUR
	MX-BFM-MX-N10-6MP BlockFlexMount 6MP, Incl. Hemispheric L10 (Night) Suitable for: S15 • HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024501 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	168,00 EUR
	MX-BFM-MX-N20-6MP-F1.8 BlockFlexMount 6MP, Incl. L20-F1.8 (Night) Suitable for: S15 • HD premium lens L20/B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024518 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	168,00 EUR
	MX-BFM-MX-N22-6MP-F1.8 BlockFlexMount 6MP, Incl. L22-F1.8 (Night) Suitable for: S15 • HD premium lens L22/B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024525 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	168,00 EUR
	MX-BFM-MX-N32-6MP-F1.8 BlockFlexMount 6MP, Incl. L32-F1.8 (Night) Suitable for: S15 • HD premium lens L32/B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024532 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	168,00 EUR
	MX-BFM-MX-N43-6MP-F1.8 BlockFlexMount 6MP, Incl. L43-F1.8 (Night) Suitable for: S15 • HD premium lens L43/B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024549 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	168,00 EUR
	MX-BFM-MX-N65-6MP-F1.8 BlockFlexMount 6MP, Incl. L65-F1.8 (Night) Suitable for: S15 • HD premium lens L65/B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024556 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	168,00 EUR

	MX-BFM-MX-N135-6MP-F1.8 BlockFlexMount 6MP, Incl. L135-F1.8 (Night) Suitable for: S15 • HD premium lens L135/B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024563 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	168,00 EUR
	MX-BFM-MX-N270-6MP BlockFlexMount 6MP, Incl. L270 (Night) Suitable for: S15 • HD premium lens L270/B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024570 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	168,00 EUR
	MX-BFM-CS-N-6MP BlockFlexMount 6MP, For CS Mount Lens (Night) Suitable for: S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024402 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	148,00 EUR
	MX-BFM-MX-N20-LPF-6MP-F1.8 BlockFlexMount 6MP, Incl. L20-F1.8 (Night LPF) Suitable for: S15 • HD premium lens L20/B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024587 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	268,00 EUR
	MX-BFM-MX-N22-LPF-6MP-F1.8 BlockFlexMount 6MP, Incl. L22-F1.8 (Night LPF) Suitable for: S15 • HD premium lens L22/B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024594 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	268,00 EUR
	MX-BFM-MX-N32-LPF-6MP-F1.8 BlockFlexMount 6MP, Incl. L32-F1.8 (Night LPF) Suitable for: S15 • HD premium lens L32/B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024600 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	268,00 EUR
	MX-BFM-MX-N43-LPF-6MP-F1.8 BlockFlexMount 6MP, Incl. L43-F1.8 (Night LPF) Suitable for: S15 • HD premium lens L43/B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024617 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	268,00 EUR
	MX-BFM-MX-N65-LPF-6MP-F1.8 BlockFlexMount 6MP, Incl. L65-F1.8 (Night LPF) Suitable for: S15 • HD premium lens L65/B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024624 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	268,00 EUR

**MX-BFM-MX-N135-LPF-6MP-F1.8****BlockFlexMount 6MP, Incl. L135-F1.8 (Night LPF)**

Suitable for: S15 • HD premium lens L135/B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438024631	10,5 cm	C	268,00	EUR
90021900	8,5 cm			
155 g	5,0 cm			

**MX-BFM-MX-N270-LPF-6MP****BlockFlexMount 6MP, Incl. 270 (Night LPF)**

Suitable for: S15 • HD premium lens L270/B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438024648	10,5 cm	C	268,00	EUR
90021900	8,5 cm			
155 g	5,0 cm			

**MX-BFM-CS-N-LPF-6MP****BlockFlexMount 6MP, For CS Mount Lens (Night LPF)**



Suitable for: S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438024419	10,5 cm	C	248,00	EUR
90021900	8,5 cm			
155 g	5,0 cm			







BlockFlexMounts S15 5MP Premium

For Individual Mounting Solutions. Extension Of The S15D System.

One or two BlockFlexMount sensor modules are connected to the S15 with a sensor cable just like the standard sensor modules. Each BlockFlexMount contains a microphone and status LEDs. Protection class IP30 (protected against access with a tool). Ambient temperature range: 0°C to +50°C/32°F to 122°F. Also available as LPF and CS mount versions.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-BFM-MX-D12	4047438019538	10,5 cm	C	118,00 EUR
	BlockFlexMount 5MP, Incl. Hemispheric L12 (Day)	90021900	8,5 cm		
	Suitable for: S15 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens (included): L12 Hemispheric (horizontal image angle 180°) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm		
	MX-BFM-MX-D23-F1.8	4047438022330	10,5 cm	C	118,00 EUR
	BlockFlexMount 5MP, Incl. L23-F1.8 (Day)	90021900	8,5 cm		
	Suitable for: S15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), color (day) • HD Premium lens (incl.) L23 super wide-angle (f/1.8, horizontal image angle 92°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm		
	MX-BFM-MX-D25-F1.8	4047438022132	10,5 cm	C	118,00 EUR
	BlockFlexMount 5MP, Incl. L25-F1.8 (Day)	90021900	8,5 cm		
	Suitable for: S15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), color (day) • HD Premium lens (incl.) L25 super wide-angle (f/1.8, horizontal image angle 82°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm		
	MX-BFM-MX-D38-F1.8	4047438024150	10,5 cm	C	118,00 EUR
	BlockFlexMount 5MP, Incl. L38-F1.8 (Day)	90021900	8,5 cm		
	Suitable for: S15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), color (day) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens (incl.): L38 wide-angle (f/1.8, horizontal image angle 55°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm		
	MX-BFM-MX-D51-F1.8	4047438024167	10,5 cm	C	118,00 EUR
	BlockFlexMount 5MP, Incl. L51-F1.8 (Day)	90021900	8,5 cm		
	Suitable for: S15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), color (day) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens (incl.): L51 wide-angle (f/1.8, horizontal image angle 40°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm		
	MX-BFM-MX-D76-F1.8	4047438024174	10,5 cm	C	118,00 EUR
	BlockFlexMount 5MP, Incl. L76-F1.8 (Day)	90021900	8,5 cm		
	Suitable for: S15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), color (day) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens (incl.): L76 tele (f/1.8, horizontal image angle 27°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm		
	MX-BFM-MX-D160-F1.8	4047438024181	10,5 cm	C	118,00 EUR
	BlockFlexMount 5MP, Incl. L160-F1.8 (Day)	90021900	8,5 cm		
	Suitable for: S15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), color (day) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens (incl.): L160 tele (f/1.8, horizontal image angle 13°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm		

	MX-BFM-MX-D320	4047438020992	10,5 cm	C	118,00	EUR
	BlockFlexMount 5MP, Incl. L320 (Day)	90021900	8,5 cm			
	Suitable for: S15 • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L320 super-telephoto (horizontal image angle 7°) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Non-reflective lens protection layer made of tempered glass • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm			
	MX-BFM-MX-N12	4047438019590	10,5 cm	C	118,00	EUR
	BlockFlexMount 5MP, Incl. Hemispheric L12 (Night)	90021900	8,5 cm			
	Suitable for: S15 • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens (included): L12 Hemispheric (horizontal image angle 180°) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm			
	MX-BFM-MX-N23-F1.8	4047438022347	10,5 cm	C	118,00	EUR
	BlockFlexMount 5MP, Incl. L23-F1.8 (Night)	90021900	8,5 cm			
	Suitable for: S15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • HD Premium lens (incl.): L23 super wide-angle (f/1.8, horizontal image angle 82°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm			
	MX-BFM-MX-N25-F1.8	4047438022149	10,5 cm	C	118,00	EUR
	BlockFlexMount 5MP, Incl. L25-F1.8 (Night)	90021900	8,5 cm			
	Suitable for: S15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • HD Premium lens (incl.): L25 super wide-angle (f/1.8, horizontal image angle 82°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm			
	MX-BFM-MX-N38-F1.8	4047438024198	10,5 cm	C	118,00	EUR
	BlockFlexMount 5MP, Incl. L38-F1.8 (Night)	90021900	8,5 cm			
	Suitable for: S15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens (incl.): L38 wide-angle (f/1.8, horizontal image angle 55°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm			
	MX-BFM-MX-N51-F1.8	4047438024204	10,5 cm	C	118,00	EUR
	BlockFlexMount 5MP, Incl. L51-F1.8 (Night)	90021900	8,5 cm			
	Suitable for: S15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens (incl.): L51 wide-angle (f/1.8, horizontal image angle 40°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm			
	MX-BFM-MX-N76-F1.8	4047438024211	10,5 cm	C	118,00	EUR
	BlockFlexMount 5MP, Incl. L76-F1.8 (Night)	90021900	8,5 cm			
	Suitable for: S15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens (incl.): L76 tele (f/1.8, horizontal image angle 27°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm			
	MX-BFM-MX-N160-F1.8	4047438024228	10,5 cm	C	118,00	EUR
	BlockFlexMount 5MP, Incl. L160-F1.8 (Night)	90021900	8,5 cm			
	Suitable for: S15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens (incl.): L160 tele (f/1.8, horizontal image angle 13°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	155 g	5,0 cm			

	MX-BFM-MX-N320 BlockFlexMount 5MP, Incl. L320 (Night) Suitable for: S15 • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens (included): L320 super-telephoto (horizontal image angle 7°) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Non-reflective lens protection layer made of tempered glass • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438021005 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	118,00 EUR
	MX-BFM-MX-N23-LPF-F1.8 BlockFlexMount 5MP, Incl. L23-F1.8 (Night LPF) Suitable for: S15 • LPF special optic: e.g., for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • HD Premium lens (incl.): L25 super wide-angle (f/1.8, horizontal image angle 92°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438022354 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	218,00 EUR
	MX-BFM-MX-N25-LPF-F1.8 BlockFlexMount 5MP, Incl. L25-F1.8 (Night LPF) Suitable for: S15 • LPF special optic: e.g., for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • HD Premium lens (incl.): L25 super wide-angle (f/1.8, horizontal image angle 82°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438022156 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	218,00 EUR
	MX-BFM-MX-N38-LPF-F1.8 BlockFlexMount 5MP, Incl. L38-F1.8 (Night LPF) Suitable for: S15 • LPF special optic: e.g., for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens (incl.): L38 wide-angle (f/1.8, horizontal image angle 55°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024235 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	218,00 EUR
	MX-BFM-MX-N51-LPF-F1.8 BlockFlexMount 5MP, Incl. L51-F1.8 (Night LPF) Suitable for: S15 • LPF special optic: e.g., for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens (incl.): L51 wide-angle (f/1.8, horizontal image angle 40°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024242 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	218,00 EUR
	MX-BFM-MX-N76-LPF-F1.8 BlockFlexMount 5MP, Incl. L76-F1.8 (Night LPF) Suitable for: S15 • LPF special optic: e.g., for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens (incl.): L76 tele (f/1.8, horizontal image angle 27°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024259 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	218,00 EUR
	MX-BFM-MX-N160-LPF-F1.8 BlockFlexMount 5MP, Incl. L160-F1.8 (Night LPF) Suitable for: S15 • LPF special optic: e.g., for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • Max. image size: 5MP (2592 x 1944 pixels) • HD Premium lens (incl.): L160 tele (f/1.8, horizontal image angle 13°) • IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438024266 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	218,00 EUR
	MX-BFM-MX-N320-LPF BlockFlexMount 5MP, Incl. L320 (Night LPF) Suitable for: S15 • LPF special optic: e.g., for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens (included): L320 super-telephoto (horizontal image angle 7°) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438021067 90021900 155 g	10,5 cm 8,5 cm 5,0 cm	C	218,00 EUR

Lens Units D15 6MP

Modular Design. Lens Units With 6MP Moonlight Sensor Technology.

The D15 is characterized by complete modularity. Choose from available lens carriers (pano, fix), lens units, all fully adjustable in any direction within the camera. This flexibility, combined with the dual-lens system, provides practically unlimited viewing options from one camera.

The D15 body, the lens carrier (pano, day & night) as well as sensor (day/night) and lenses (from tele to wide angle) can be used in nearly any combination. Therefore existing D15 models can be easily equipped and re-built. Here you can find the complete choice of D15 lens units and carriers.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
 	MX-D15-SM-FIX	4047438027489	10,5 cm	C	180,00 EUR
	D15 Double Lens Carrier FIX, 2x 6MP (Day & Night) Day & Night Double Lens Carrier for D15 Body, including two parallel aligned 6MP sensors (1x Day, 1x Night), lenses not included (two lenses MX-B036 to MX-B237 possible, to be ordered separately)	125 g	6,8 cm 10,5 cm		
 	MX-D15-SM-PAN	4047438027496	10,5 cm	C	180,00 EUR
	D15 Double Lens Carrier PAN/180°, 2x 6MP (Day) Panorama/180° Double Lens Carrier for D15 Body, including two day sensors 6MP, lenses not included (two lenses MX-B041 needed for 180° panoramic image, to be ordered separately)	125 g	6,8 cm 10,5 cm		
 	MX-D15-SM-PAN-N	4047438027502	10,5 cm	C	180,00 EUR
	D15 Double Lens Carrier PAN-N/180°, 2x 6MP (Night) Panorama/180° Double Lens Carrier for D15 Body, including two night sensors 6MP, lenses not included (two lenses MX-B041 needed for 180° panoramic image, to be ordered separately)	125 g	6,8 cm 10,5 cm		
 	MX-D15-Module-D20-6MP-F1.8	4047438023054	9,0 cm	C	150,00 EUR
	Lens Unit D15 6MP, Incl. L20-F1.8 (Day)	90021900	6,0 cm		
	Lens unit D15 with HD premium lens L20/B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)	64 g	4,0 cm		
 	MX-D15-Module-D22-6MP-F1.8	4047438023061	9,0 cm	C	150,00 EUR
	Lens Unit D15 6MP, Incl. L22-F1.8 (Day)	90021900	6,0 cm		
	Lens unit D15 with HD premium lens L22/B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048)	64 g	4,0 cm		
 	MX-D15-Module-D32-6MP-F1.8	4047438023078	9,0 cm	C	150,00 EUR
	Lens Unit D15 6MP, Incl. L32-F1.8 (Day)	90021900	6,0 cm		
	Lens unit D15 with HD premium lens L32/B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048)	64 g	4,0 cm		

 	MX-D15-Module-D43-6MP-F1.8 Lens Unit D15 6MP, Incl. L43-F1.8 (Day) Lens unit D15 with HD premium lens L43/B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438023085 90021900 64 g	9,0 cm 6,0 cm 4,0 cm	C	150,00 EUR
 	MX-D15-Module-D65-6MP-F1.8 Lens Unit D15 6MP, Incl. L65-F1.8 (Day) Lens unit D15 with HD premium lens L65/B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438023092 90021900 64 g	9,0 cm 6,0 cm 4,0 cm	C	150,00 EUR
 	MX-D15-Module-D135-6MP-F1.8 Lens Unit D15 6MP, Incl. L135-F1.8 (Day) Lens unit D15 with HD premium lens L135/B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438023108 90021900 64 g	9,0 cm 6,0 cm 4,0 cm	C	150,00 EUR
 	MX-D15-Module-N20-6MP-F1.8 Lens Unit D15 6MP, Incl. L20-F1.8 (Night) Lens unit D15 with HD premium lens L20/B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438023115 90021900 64 g	9,0 cm 6,0 cm 4,0 cm	C	150,00 EUR
 	MX-D15-Module-N22-6MP-F1.8 Lens Unit D15 6MP, Incl. L22-F1.8 (Night) Lens unit D15 with HD premium lens L22/B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048)	4047438023122 90021900 64 g	9,0 cm 6,0 cm 4,0 cm	C	150,00 EUR
 	MX-D15-Module-N32-6MP-F1.8 Lens Unit D15 6MP, Incl. L32-F1.8 (Night) Lens unit D15 with HD premium lens L32/B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048)	4047438023139 90021900 64 g	9,0 cm 6,0 cm 4,0 cm	C	150,00 EUR
 	MX-D15-Module-N43-6MP-F1.8 Lens Unit D15 6MP, Incl. L43-F1.8 (Night) Lens unit D15 with HD premium lens L43/B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048)	4047438023146 90021900 64 g	9,0 cm 6,0 cm 4,0 cm	C	150,00 EUR
 	MX-D15-Module-N65-6MP-F1.8 Lens Unit D15 6MP, Incl. L65-F1.8 (Night) Lens unit D15 with HD premium lens L65/B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048)	4047438023153 90021900 64 g	9,0 cm 6,0 cm 4,0 cm	C	150,00 EUR

 	MX-D15-Module-N135-6MP-F1.8 Lens Unit D15 6MP, Incl. L135-F1.8 (Night) Lens unit D15 with HD premium lens L135/B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048)	4047438023160 90021900 64 g	9,0 cm 6,0 cm 4,0 cm	C	150,00 EUR
 	MX-D15-Module-N20-LPF-6MP-F1.8 Lens Unit D15 6MP, Incl. L20-F1.8 (Night LPF) Lens unit D15 with HD premium lens L20/B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)	4047438023177 90021900 64 g	9,0 cm 6,0 cm 4,0 cm	C	250,00 EUR
 	MX-D15-Module-N22-LPF-6MP-F1.8 Lens Unit D15 6MP, Incl. L22-F1.8 (Night LPF) Lens unit D15 with HD premium lens L22/B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)	4047438023184 90021900 64 g	9,0 cm 6,0 cm 4,0 cm	C	250,00 EUR
 	MX-D15-Module-N32-LPF-6MP-F1.8 Lens Unit D15 6MP, Incl. L32-F1.8 (Night LPF) Lens unit D15 with HD premium lens L32/B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)	4047438023191 90021900 64 g	9,0 cm 6,0 cm 4,0 cm	C	250,00 EUR
 	MX-D15-Module-N43-LPF-6MP-F1.8 Lens Unit D15 6MP, Incl. L43-F1.8 (Night LPF) Lens unit D15 with HD premium lens L43/B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)	4047438023207 90021900 64 g	9,0 cm 6,0 cm 4,0 cm	C	250,00 EUR
 	MX-D15-Module-N65-LPF-6MP-F1.8 Lens Unit D15 6MP, Incl. L65-F1.8 (Night LPF) Lens unit D15 with HD premium lens L65/B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)	4047438023214 90021900 64 g	9,0 cm 6,0 cm 4,0 cm	C	250,00 EUR
 	MX-D15-Module-N135-LPF-6MP-F1.8 Lens Unit D15 6MP, Incl. L135-F1.8 (Night LPF) Lens unit D15 with HD premium lens L135/B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)	4047438023221 90021900 64 g	9,0 cm 6,0 cm 4,0 cm	C	250,00 EUR

Lens Units D15 5MP Premium

Complete Lens Units. Consisting Of A 5MP Sensor Plus Lens.

The lens units can be installed in the D15 camera housing (body) and focused precisely on the monitored area. One lens unit is equipped with one 5MP color or B/W sensor and one MOBOTIX Premium lens from super-wide angle to telephoto. Two lens units of your choice can be used in every D15, meaning all day/day, night/night and day/night combinations are possible. Also available with Long Pass Filter (LPF) for optimal license plate identification in all lighting conditions.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-D15-Module-D23-F1.8	4047438022361	9,0 cm	C	100,00 EUR
	Lens Unit D15 5MP, Incl. L23-F1.8 (Day)	90021900	6,0 cm		
	Suitable for: D15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), color (day) • HD Premium lens L23 super wide-angle (f/1.8, horizontal image angle 92°)	64 g	4,0 cm		
	MX-D15-Module-D25-F1.8	4047438022163	9,0 cm	C	100,00 EUR
	Lens Unit D15D 5MP, Incl. L25-F1.8 (Day)	90021900	6,0 cm		
	Suitable for: D15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), color (day) • HD Premium lens L25 super wide-angle (f/1.8, horizontal image angle 82°)	64 g	4,0 cm		
	MX-D15-Module-D38-F1.8	4047438023924	9,0 cm	C	100,00 EUR
	Lens Unit D15 5MP, Incl. L38-F1.8 (Day)	90021900	6,0 cm		
	Suitable for: D15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), color (day) • HD Premium lens L38 wide-angle (f/1.8, horizontal image angle 55°)	64 g	4,0 cm		
	MX-D15-Module-D51-F1.8	4047438023931	9,0 cm	C	100,00 EUR
	Lens Unit D15 5MP, Incl. L51-F1.8 (Day)	90021900	6,0 cm		
	Suitable for: D15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), color (day) • HD Premium lens L51 wide-angle (f/1.8, horizontal image angle 40°)	64 g	4,0 cm		
	MX-D15-Module-D76-F1.8	4047438023948	9,0 cm	C	100,00 EUR
	Lens Unit D15 5MP, Incl. L76-F1.8 (Day)	90021900	6,0 cm		
	Suitable for: D15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), color (day) • HD Premium lens L76 tele (f/1.8, horizontal image angle 27°)	64 g	4,0 cm		
	MX-D15-Module-D160-F1.8	4047438023955	9,0 cm	C	100,00 EUR
	Lens Unit D15 5MP, Incl. L160-F1.8 (Day)	90021900	6,0 cm		
	Suitable for: D15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), color (day) • HD Premium lens L160 tele (f/1.8, horizontal image angle 13°)	64 g	4,0 cm		
	MX-D15-Module-N23-F1.8	4047438022378	9,0 cm	C	100,00 EUR
	Lens Unit D15 5MP, Incl. L23-F1.8 (Night)	90021900	6,0 cm		
	Suitable for: D15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • HD Premium lens L23 super wide-angle (f/1.8, horizontal image angle 92°)	64 g	4,0 cm		

	MX-D15-Module-N25-F1.8	4047438022170	9,0 cm	C	100,00	EUR
	Lens Unit D15 5MP, Incl. L25-F1.8 (Night)	90021900	6,0 cm			
	Suitable for: D15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • HD Premium lens L25 super wide-angle (f/1.8, horizontal image angle 82°)	64 g	4,0 cm			
	MX-D15-Module-N38-F1.8	4047438023962	9,0 cm	C	100,00	EUR
	Lens Unit D15 5MP, Incl. L38-F1.8 (Night)	90021900	6,0 cm			
	Suitable for: D15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • HD Premium lens L38 wide-angle (f/1.8, horizontal image angle 55°)	64 g	4,0 cm			
	MX-D15-Module-N51-F1.8	4047438023979	9,0 cm	C	100,00	EUR
	Lens Unit D15 5MP, Incl. L51-F1.8 (Night)	90021900	6,0 cm			
	Suitable for: D15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • HD Premium lens L51 wide-angle (f/1.8, horizontal image angle 40°)	64 g	4,0 cm			
	MX-D15-Module-N76-F1.8	4047438023986	9,0 cm	C	100,00	EUR
	Lens Unit D15 5MP, Incl. L76-F1.8 (Night)	90021900	6,0 cm			
	Suitable for: D15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • HD Premium lens L76 tele (f/1.8, horizontal image angle 27°)	64 g	4,0 cm			
	MX-D15-Module-N160-F1.8	4047438023993	9,0 cm	C	100,00	EUR
	Lens Unit D15 5MP, Incl. L76-F1.8 (Night)	90021900	6,0 cm			
	Suitable for: D15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • HD Premium lens L76 tele (f/1.8, horizontal image angle 27°)	64 g	4,0 cm			
	MX-D15-Module-N23-LPF-F1.8	4047438022385	9,0 cm	C	200,00	EUR
	Lens Unit D15 5MP, Incl. L25-F1.8 (Night LPF)	90021900	6,0 cm			
	Suitable for: D15 • LPF special optic: e.g., for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • HD Premium lens L25 super wide-angle (f/1.8, horizontal image angle 82°)	64 g	4,0 cm			
	MX-D15-Module-N25-LPF-F1.8	4047438022187	9,0 cm	C	200,00	EUR
	Lens Unit D15 5MP, Incl. L25-F1.8 (Night LPF)	90021900	6,0 cm			
	Suitable for: D15 • LPF special optic: e.g., for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • HD Premium lens L25 super wide-angle (f/1.8, horizontal image angle 82°)	64 g	4,0 cm			
	MX-D15-Module-N38-LPF-F1.8	4047438024006	9,0 cm	C	200,00	EUR
	Lens Unit D15 5MP, Incl. L38-F1.8 (Night LPF)	90021900	6,0 cm			
	Suitable for: D15 • LPF special optic: e.g., for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • HD Premium lens L38 wide-angle (f/1.8, horizontal image angle 55°)	64 g	4,0 cm			

	MX-D15-Module-N51-LPF-F1.8	4047438024013	9,0 cm	C	200,00	EUR
	Lens Unit D15 5MP, Incl. L51-F1.8 (Night LPF)	90021900	6,0 cm			
	Suitable for: D15 • LPF special optic: e.g., for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • HD Premium lens L51 wide-angle (f/1.8, horizontal image angle 40°)	64 g	4,0 cm			
	MX-D15-Module-N76-LPF-F1.8	4047438024020	9,0 cm	C	200,00	EUR
	Lens Unit D15 5MP, Incl. L76-F1.8 (Night LPF)	90021900	6,0 cm			
	Suitable for: D15 • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • HD Premium lens L76 tele (f/1.8, horizontal image angle 27°)	64 g	4,0 cm			
	MX-D15-Module-N160-LPF-F1.8	4047438024037	9,0 cm	C	200,00	EUR
	Lens Unit D15 5MP, Incl. L160-F1.8 (Night LPF)	90021900	6,0 cm			
	Suitable for: D15 • LPF special optic: e.g., for license plate identification (combined with infrared light) • Image sensor: 1/2.5" CMOS, 5 megapixels (2592 x 1944), B/W (night) • HD Premium lens L160 tele (f/1.8, horizontal image angle 13°)	64 g	4,0 cm			



Camera Accessories

All prices are Manufacturer's suggested retail prices, net, ex works. Information subject to change without notice.
HS = Harmonized System Code DG = Discount Group

MOBOTIX HD Premium Lenses

Interchangeable Lenses For p25, M25, D25 And D15.

The high-quality HD premium lenses can be used for different MOBOTIX camera series. They offer the advantage that they are also compatible with older camera series. The area captured by the lens (horizontal and vertical angle) slightly differs with the image sensor installed in the camera.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-B036	4047438026536	9,0 cm	C	60,00 EUR
	Ultra Wide Lens B036, Focal Length: 3.6 mm	90021900	6,0 cm		
	Ultra Wide lens B036 • HD premium quality • Focal length: 3.6 mm • Aperture: f/1.8	30 g	4,0 cm		
	• Image angle (horizontal x vertical, with 6MP sensor): 103° x 77° (MX Order number before June, 2015: MX-OPT-F1.8-L20-L23)				
	MX-B041	4047438026543	9,0 cm	C	60,00 EUR
	Super Wide Lens B041, Focal Length: 4.1 mm	90021900	6,0 cm		
	Super Wide lens B041 • HD premium quality • Focal length: 4.1 mm • Aperture: f/1.8	30 g	4,0 cm		
	• Image angle (horizontal x vertical, with 6MP sensor): 90° x 67° (MX Order number before June, 2015: MX-OPT-F1.8-L22-L25)				
	MX-B061	4047438026550	9,0 cm	C	60,00 EUR
	Wide Lens B061, Focal Length: 6.1 mm	90021900	6,0 cm		
	Wide lens B061 • HD premium quality • Focal length: 6.1 mm • Aperture: f/1.8 •	30 g	4,0 cm		
	Image angle (horizontal x vertical, with 6MP sensor): 60° x 45° (MX Order number before June, 2015: MX-OPT-F1.8-L32-L38)				
	MX-B079	4047438026567	9,0 cm	C	60,00 EUR
	Standard Lens B079, Focal Length: 7.9 mm	90021900	6,0 cm		
	Standard lens B079 • HD premium quality • Focal length: 7.9 mm • Aperture: f/1.8 •	30 g	4,0 cm		
	Image angle (horizontal x vertical, with 6MP sensor): 45° x 34° (MX Order number before June, 2015: MX-OPT-F1.8-L43-L51)				
	MX-B119	4047438026574	9,0 cm	C	60,00 EUR
	Tele Lens B119, Focal Length: 11.9 mm	90021900	6,0 cm		
	Tele lens B119 • HD premium quality • Focal length: 11.9 mm • Aperture: f/1.8 •	30 g	4,0 cm		
	Image angle (horizontal x vertical, with 6MP sensor): 31° x 23° (MX Order number before June, 2015: MX-OPT-F1.8-L65-L76)				
	MX-B237	4047438026581	9,0 cm	C	60,00 EUR
	Distant Tele Lens B237, Focal Length: 23.7 mm	90021900	6,0 cm		
	Distant Tele lens B237 • HD premium quality • Focal length: 23.7 mm • Aperture: f/1.8 •	30 g	4,0 cm		
	Image angle (horizontal x vertical, with 6MP sensor): 15° x 11° (MX Order number before June, 2015: MX-OPT-F1.8-L135-L160)				
	MX-B500	4047438026598	9,0 cm	C	60,00 EUR
	Super Tele Lens B500, Focal Length: 50 mm	90021900	6,0 cm		
	Super Tele lens B500 • HD premium quality • Focal length: 50 mm • Aperture: f/2.5	30 g	4,0 cm		
	• Image angle (horizontal x vertical, with 6MP sensor): 8° x 6° (MX Order number before June, 2015: MX-OPT-F1.8-L270-L320) • For mounting this lens on the M25, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL)				

	MX-B045-100-CS	4047438026604	70,0 cm	C	100,00	EUR
	CSVario Lens For Cameras With CS-Mount	90021900	50,0 cm			
	CS Vario lens B045-100-CS • HD premium quality • Variable focal length: 4,5-10 mm • Variable aperture: f/1.6-2.3 • Variable image angle (horizontal x vertical, with 6MP sensor): 39°-89° x 29°-65° (MX Order number before June, 2015: MX-OPTCS-L24-54)	60 g	50,0 cm			
	MX-SM-OPT-POL	4047438019781	8,5 cm	C	128,00	EUR
	Polarization Filter For Sensor Modules	90079100	6,0 cm			
	Suitable for all non-hemispheric sensor modules • Filter replaces the lens cover (made of glass) • Example: Recognition of people through the windshield of a car - the filter reduces the mirror reflection (and about 50 % of the sensor light sensitivity)	20 g	3,6 cm			

Domes & Housings

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-M24M-OPT-LCSK	4047438012980	9,0 cm	C	20,00 EUR
	Replacement Lens Cover M2x, Standard	90079100	6,0 cm		
	Suitable for: M2x (not for CSVario, Hemispheric or super tele lens B500) • Weather lens protection made of plastic (IP66)	26 g	4,0 cm		
	MX-M24M-OPT-LCSG	4047438012997	9,0 cm	C	30,00 EUR
	Replacement Lens Cover M2x, With Glass Pane	90079100	6,0 cm		
	Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)	34 g	4,0 cm		
	MX-M24M-OPT-LCGL	4047438013000	9,0 cm	C	30,00 EUR
	Replacement Lens Cover M2x, Extended	90079100	6,0 cm		
	Suitable for: M2x with CSVario lens B045-100-CS or super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)	50 g	4,0 cm		
	MX-OPT-DK-L11	4047438016469	8,5 cm	C	28,00 EUR
	Replacement Cover Hemispheric	90079100	6,0 cm		
	Suitable for: Hemispheric sensor modules (for S15/M15), S15M, T25 and Q25 with Vanadism Kit • Mounted with the blue MOBOTIX lens wrench (supplied with the Mx camera) • Polycarbonate (1.5 mm)	19 g	3,6 cm		
	MX-D15-OPT-DCT	4047438018227	12,0 cm	C	28,00 EUR
	Replacement Cover DualDome Cameras	90079100	12,0 cm		
	Suitable for: D1x • Not for Pano/180° and DNight-Fix models (XL cover needed)	54 g	8,0 cm		
	MX-D15-OPT-DCS	4047438018210	12,0 cm	C	28,00 EUR
	Replacement Cover DualDome Cameras, Tinted	90079100	12,0 cm		
	Suitable for: D1x • Not for Pano/180° and DNight-Fix models (XL cover needed) • Suitable for: D25, D24, D22 • Tinted (50%) for especially bright environments	54 g	8,0 cm		
	MX-D15-DCT-XL	4047438027519	12,0 cm	C	28,00 EUR
	Replacement Cover "XL" DualDome Cameras	90079100	12,0 cm		
	Suitable for: D1x Pano/180° and DNight-Fix models • Polycarbonate (1.5 mm)	60 g	9,0 cm		

	MX-D15-DCS-XL	4047438027526	12,0 cm	C	28,00	EUR
	Replacement Cover "XL" DualDome Cameras, Tinted	90079100	12,0 cm			
	Suitable for: D1x Pano/180° and DNight-Fix models • Tinted (50%) for especially bright environments • Polycarbonate (1.5 mm)	60 g	9,0 cm			
	MX-D24M-OPT-DCT	4047438011419	12,0 cm	C	29,00	EUR
	Replacement Cover Dome Cameras	90079100	12,0 cm			
	Suitable for: D25, D24, D22 • With sealing ring	54 g	8,0 cm			
	MX-D24M-OPT-DCS	4047438011402	12,0 cm	C	29,00	EUR
	Replacement Cover Dome Cameras, Tinted	90079100	12,0 cm			
	Suitable for: D25, D24, D22 • With sealing ring • Tinted (50%) for especially bright environments	54 g	8,0 cm			
	MX-D15-Vandal-ESMA	4047438018173	30,5 cm	C	148,00	EUR
	Vandalism Kit DualDome Cameras, Matt	90079100	23,5 cm			
	Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models	1.116 g	16,0 cm			
	MX-D15-Vandal-ESPO	4047438018166	30,5 cm	C	148,00	EUR
	Vandalism Kit DualDome Cameras, Polished	90079100	23,5 cm			
	Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models	1.116 g	16,0 cm			
	MX-D15-Vandal-PUBL	4047438018203	30,5 cm	C	148,00	EUR
	Vandalism Kit DualDome Cameras, Black	90079100	23,5 cm			
	Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models	1.116 g	16,0 cm			
	MX-D15-Vandal-PUGR	4047438018180	30,5 cm	C	148,00	EUR
	Vandalism Kit DualDome Cameras, Gray	90079100	23,5 cm			
	Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models	1.116 g	16,0 cm			
	MX-D15-Vandal-PUWH	4047438018197	30,5 cm	C	148,00	EUR
	Vandalism Kit DualDome Cameras, White	90079100	23,5 cm			
	Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models	1.116 g	16,0 cm			

	MX-D15-DCT-V	4047438027533	12,0 cm	C	38,00	EUR
	Replacement Cover "Vandalism" DualDome Cameras	90079100	12,0 cm			
	Reinforced replacement cover (polycarbonate, 3 mm) for D1x Vandalism Kits • Not suitable for D1x Pano/180° and DNight-Fix models (XL cover needed)	60 g	8,0 cm			
	MX-D24M-Vandal-ESMA	4047438011143	31,0 cm	C	98,00	EUR
	Vandalism Kit Dome Cameras, Matt	90079100	24,0 cm			
	Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)	672 g	12,0 cm			
	MX-D24M-Vandal-ESPO	4047438011150	31,0 cm	C	98,00	EUR
	Vandalism Kit Dome Cameras, Polished	90079100	24,0 cm			
	Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)	668 g	12,0 cm			
	MX-D24M-Vandal-PUBL	4047438011181	31,0 cm	C	98,00	EUR
	Vandalism Kit Dome Cameras, Black	90079100	24,0 cm			
	Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)	676 g	12,0 cm			
	MX-D24M-Vandal-PUGR	4047438011174	31,0 cm	C	98,00	EUR
	Vandalism Kit Dome Cameras, Gray	90079100	24,0 cm			
	Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)	676 g	12,0 cm			
	MX-D24M-Vandal-PUWH	4047438011167	31,0 cm	C	98,00	EUR
	Vandalism Kit Dome Cameras, White	90079100	24,0 cm			
	Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)	682 g	12,0 cm			
	MX-D25-DCT-V	4047438027700	12,0 cm	C	38,00	EUR
	Replacement Cover "Vandalism" Dome Cameras	90079100	12,0 cm			
	Reinforced replacement cover (polycarbonate, 3 mm) for D2x Vandalism Kits • With sealing ring	60 g	8,0 cm			
	MX-Q24M-Vandal-ESMA	4047438011273	30,5 cm	C	198,00	EUR
	Vandalism Set Q2x, Stainless Steel Matt	90079100	23,5 cm			
	Suitable for: Q2x • Vandalism-proof housing with lens protection • Ideally suited for surveillance at extremely critical locations • Raises camera protection class to IP66 and IK10 • Stainless steel, finish matt • Incl. security screws • Incl. 3 reinforced domes (3 mm polycarbonate) • Audio features still available	736 g	12,0 cm			

**MX-Q24M-Vandal-ESPO****Vandalism Set Q2x, Stainless Steel Polished**

Suitable for: Q2x • Vandalism-proof housing with lens protection • Ideally suited for surveillance at extremely critical locations • Raises camera protection class to IP66 and IK10 • Stainless steel, finish polished • Incl. security screws • Incl. 3 reinforced domes (3 mm polycarbonate) • Audio features still available

4047438011280	30,5 cm	C	198,00	EUR
90079100	23,5 cm			
756 g	12,0 cm			

Mounts S15

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-FLEX-OPT-DM-PW	4047438017626	19,0 cm	C	38,00 EUR
	DualMount S1x, White	90079100	23,0 cm		
	For surveillance of one area with two sensor modules (in particular, for day and night) • Suitable for all available sensor modules of the S15 (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: White	442 g	8,5 cm		
	MX-FLEX-OPT-SM-PW	4047438016407	19,0 cm	C	38,00 EUR
	SurroundMount S1x, White	90079100	23,0 cm		
	For surveillance of long and narrow spaces (e.g., bus, train, hallway, etc.) without blind spots • Two sensor modules of the S15 can be integrated in the mount (not included) • For all 5MP and 6MP Sensor modules • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: White	463 g	8,5 cm		
	MX-PTMount-OPT-PW	4047438021166	16,0 cm	C	58,00 EUR
	PTMount S1x, White	90079100	13,0 cm		
	Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideways tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all available sensor modules for S1x (MX-SM-Dxx or MX-SM-Nxx) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: white	610 g	13,0 cm		
	MX-FLEX-OPT-DM-BL	4047438021869	19,0 cm	C	38,00 EUR
	DualMount S1x, Black	90079100	23,0 cm		
	For surveillance of one area with two sensor modules (in particular, for day and night) • Suitable for all available sensor modules of the S15D (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	442 g	8,5 cm		
	MX-FLEX-OPT-SM-BL	4047438021845	19,0 cm	C	38,00 EUR
	SurroundMount S1x, Black	90079100	23,0 cm		
	For surveillance of long and narrow spaces (e.g., bus, train, hallway, etc.) without blind spots • Two sensor modules of the S15D can be integrated in the mount (not included) • For all 5MP and 6MP Sensor modules • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	463 g	8,5 cm		
	MX-PTMount-OPT-BL	4047438021852	16,0 cm	C	58,00 EUR
	PTMount S1x, Black	90079100	13,0 cm		
	Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideways tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all available sensor modules for S1x (MX-SM-Dxx or MX-SM-Nxx) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: black	610 g	13,0 cm		
	MX-HALO-EXT-PW	4047438017664	12,0 cm	C	32,00 EUR
	HaloMount S1x, White	90079100	13,0 cm		
	Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)	175 g	4,0 cm		

	MX-HALO-EXT-BL HaloMount S1x, Black Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W) •	4047438017671 90079100 175 g	12,0 cm 13,0 cm 4,0 cm	C	32,00 EUR
	MX-HALO-EXT-CM HaloMount S1x, Matt Chrome Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)	4047438017633 90079100 175 g	12,0 cm 13,0 cm 4,0 cm	C	32,00 EUR
	MX-HALO-EXT-CO HaloMount S1x, Chrome Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)	4047438017640 90079100 175 g	12,0 cm 13,0 cm 4,0 cm	C	32,00 EUR
	MX-HALO-EXT-NG HaloMount S1x, Brushed Nickel Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)	4047438017657 90079100 175 g	12,0 cm 13,0 cm 4,0 cm	C	32,00 EUR
	MX-HALO-SP-EXT-PW SpeakerMount S1x, White Integrated speaker incl. mount, white • Suitable for the installation in ceilings or walls, indoor (IP20) • Compatible with all cameras S1x and V15 • Direct connection via two-wire cable, no additional power supply unit needed • Inner ring with speaker can be tilted up to 20° • Temperature range: -30 to 60°C/-22 to 140°F • IP code: IP20 • impedance: 8 ohm • Speaker material: metall with perforated plate covering • Connection type: two-wired strand, clamp included	4047438017688 85182200 273 g	12,0 cm 13,0 cm 4,0 cm	C	128,00 EUR
	MX-HALO-SP-EXT-CM SpeakerMount S1x, Matt Chrome Integrated speaker incl. mount, matt chrome • Suitable for the installation in ceilings or walls, indoor (IP20) • Compatible with all cameras S1x and V15 • Direct connection via two-wire cable, no additional power supply unit needed • Inner ring with speaker can be tilted up to 20° • Temperature range: -30 to 60°C/-22 to 140°F • IP code: IP20 • impedance: 8 ohm • Speaker material: metall with perforated plate covering • Connection type: two-wired strand, clamp included	4047438017695 85182200 273 g	12,0 cm 13,0 cm 4,0 cm	C	128,00 EUR
	MX-S14-OPT-MK-CW Extension Set Sensor Module, 40 mm And 15° Complete set for wall or ceiling mounting of a sensor module using 15° wedges • Incl. extension to increase the installation depth • Suitable for all S1x sensor modules • 1x extension 40 mm/1.6 in • 2x 15° wedges (white and black) • 2x wedge sealing rings • 1x nut	4047438016384 90079100 134 g	21,2 cm 8,5 cm 8,7 cm	C	28,00 EUR
	MX-S14-OPT-MK-EX Extension Sensor Module, 40 mm 1x extension 40 mm/1.6 inch, increases the installation depth • Suitable for all S1x sensor modules • Can be mounted directly onto the sensor modules themselves or onto existing extensions	4047438016391 90079100 62 g	10,3 cm 6,5 cm 10,3 cm	C	18,00 EUR

**MX-FLEX-OPT-AM-BL****AudioMount S1xM, Self-Adhesive**

Suitable for: S15M, S14M • Easy, quick and concealed mounting with adhesive foil (e. g. behind a stainless steel plate) • Speaker and microphone with camera connection cable included • Use of the camera as a door station by connecting a bell module

4047438019873	24,0 cm	C	48,00	EUR
85299065	13,6 cm			
386 g	5,3 cm			

Camera Mounts

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-MT-TUBE	4047438027557	20,5 cm	C	58,00 EUR
	MxTubeMount Ceiling Suspension System	90079100	20,0 cm		
	For suspended ceiling installation of the cameras M15/M25/v25/PTMount/PT-Mount-Thermal (each can be attached directly to the MxTubeMount) and of the cameras D25/Q25/c25/p25 (each can only be attached to the MxTubeMount when using the optional on-wall mounting set of the camera) • Incl. drop down protection	500 g	12,5 cm		
	• Additionally needed suspension tube MxTube with a length of 1m (3.3 ft) or 2 m (6.6 ft) to be ordered separately (MX-MT-TUBE100, MX-MT-TUBE200) • Alternative suspension with customary tubes: outer diameter 30 mm or 26.9 mm (R3/4" according to DIN 2440), max. length: 2 m (6.6 ft), max. weight: 2.5 kg (5.5 lb), color/material of choice				
	MX-MT-TUBE100	4047438027687	105,0 cm	C	40,00 EUR
	MxTube, 1 m	90079100	4,0 cm		
	Suspension tube for MxTubeMount • Length: 1 m (3.3 ft) • Anodized aluminium • Outer diameter: 30 mm, wall thickness: 2 mm	500 g	4,0 cm		
	MX-MT-TUBE200	4047438027564	205,0 cm	C	58,00 EUR
	MxTube, 2 m	90079100	4,0 cm		
	Suspension tube for MxTubeMount • Length: 2 m (6.6 ft) • Anodized aluminium • Outer diameter: 30 mm, wall thickness: 2 mm	1.000 g	4,0 cm		
	MX-OPT-UP1	4047438022118	15,0 cm	C	28,00 EUR
	Cavity Wall Installation Set i25	90079100	15,0 cm		
	Cavity Wall Installation Set for the i25 • With cavity wall socket, stainless steel mounting plate, 2 Allen screws with washers • For installing the camera directly on the mounting plate, no dowels required • Mounting plate is screwed onto the cavity wall socket • Recommended only for wall installations	116 g	6,5 cm		
	MX-OPT-AP2	4047438025898	14,0 cm	C	28,00 EUR
	On-Wall Mounting Set i25, 25 mm	90079100	14,5 cm		
	Suitable for: i25 • Consists of on-wall mount and mounting parts • Enables on-wall cabling of the camera • Camera distance from the wall: ca. 25 mm • Recommended only for wall installation • Color: white	96 g	3,5 cm		
	MX-MT-OW-1	4047438027083	30,5 cm	C	48,00 EUR
	On-Wall Mounting Set c25/p25	90079100	23,5 cm		
	Suitable for: c25 und p25 • Consists of on-wall mount and mounting parts • Enables on-wall cabling of the camera and integrates additional modules (e.g. two Interface Boxes) • Camera distance from the wall: ca. 80 mm • Diameter: 140 mm • Recommended only for ceiling installation • Color: White	700 g	16,0 cm		
	MX-MT-CM-1	4047438027076	30,5 cm	C	38,00 EUR
	Corner Mounting Set c25	90079100	23,5 cm		
	Suitable for: c25 • Consists of on-wall mount and mounting parts • Mounting in a room corner • Mounting position plus 35° tilt angle enable one camera (e.g. c25 with lens B036) to capture an entire room • Color: White	600 g	16,0 cm		

	MX-MT-v25-V	4047438027601	20,5 cm	C	98,00	EUR
	Vandalism Kit For v25	90079100	20,0 cm			
	Suitable for: v25 without On-Wall Set with Audio • Stainless steel vandalism ring (matt) with safety screws • Protects the camera housing (only without On-Wall Set) • Reinforced lens cover (polycarbonate, 3 mm)	350 g	12,5 cm			
	MX-OPT-AP	4047438011358	30,5 cm	C	98,00	EUR
	On-Wall Set Q2x/D2x/ExtIO	90079100	23,5 cm			
	Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts • Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x 37 mm	750 g	11,5 cm			
	MX-OPT-AP-10DEG	4047438010283	30,5 cm	C	98,00	EUR
	10° On-Wall Set Q2x/D2x/ExtIO	90079100	23,5 cm			
	Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts • Camera can be mounted at a 10° tilt angle • Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x 37 mm	712 g	12,0 cm			
	MX-D15-OPT-WHMH-Set	4047438018159	68,0 cm	C	198,00	EUR
	Wall/Pole Mount Set DualDome Cameras (For IP65)	90079100	32,0 cm			
	Suitable for: D1x • Set consisting of pole/corner mount (MX-MH-Dome-ESWS) and wall mount (MX-WH-Dome) • Mounted to the corner, one camera can cover two sides of a building simultaneously • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Wall mount raises camera protection class from IP54 to IP65 • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm	5.000 g	23,0 cm			
	MX-OPT-WHMH-Set	4047438011396	30,5 cm	C	168,00	EUR
	Wall/Pole Mount Set Q2x/D2x/ExtIO	90079100	23,5 cm			
	Suitable for: Q2x, D2x, ExtIO • Set consisting of pole/corner mount (MX-OPT-MH) and wall mount (MX-OPT-WH) • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm	2.410 g	16,0 cm			
	MX-WH-Dome	4047438002233	32,0 cm	C	148,00	EUR
	Wall Mount Set DualDome Cameras (For IP65)	90079100	30,5 cm			
	Suitable for: D1x • Shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Raises camera protection class from IP54 to IP66 • Incl. mounting parts	2.000 g	23,0 cm			
	MX-OPT-WH	4047438011372	30,5 cm	C	98,00	EUR
	Wall Mount Q2x/D2x/ExtIO	90079100	23,5 cm			
	Suitable for: Q2x, D2x, ExtIO • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts	1.040 g	16,0 cm			

	MX-WH-SecureFlex	4047438002219	20,0 cm	C	48,00	EUR
	SecureFlex Wall & Ceiling Mount M12/M10/M1	90079100	15,0 cm			
	Suitable for: M12/M10/M1 • Shock-resistant fiberglass-reinforced composite (PBT), white • Patented tamper-proof concealed cabling • Can be turned left/right 90°, tilted downwards 70° • Includes stainless steel mounting set, caps and dowels	390 g	11,0 cm			
	MX-MH-Dome-ESWS	4047438002240	34,0 cm	C	98,00	EUR
	Corner & Pole Mount Set DualDome Cameras	90079100	18,0 cm			
	Suitable for: D1x • Pole/corner mount for fastening of wall mount (to be ordered individually) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm	3.000 g	11,0 cm			
	MX-MH-SecureFlex-ESWS	4047438002226	20,0 cm	C	78,00	EUR
	Pole Mount For M1x/M2x	90079100	7,0 cm			
	Suitable for: M1x, M2x • Mount for fastening the wall mounts SecureFlex (M12/M10, M22) and VarioFlex (M15, M2x) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm	1.230 g	15,0 cm			
	MX-OPT-MH	4047438011389	34,0 cm	C	98,00	EUR
	Pole Mount, Accessory For MX-OPT-WH	90079100	18,5 cm			
	Mount for fastening the wall mount MX-OPT-WH (to be ordered separately) • A set consisting of pole mount and wall mount is also available (MX-OPT-WHMA-Set) • Suitable for: Q2x, D2x, ExtIO • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm	1.370 g	11,5 cm			
	MX-OPT-IC-BL	4047438013970	30,5 cm	C	98,00	EUR
	In-Ceiling Set Q2x, Black	90079100	23,5 cm			
	Special model for the Q2x with black housing • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm	550 g	16,0 cm			
	MX-OPT-IC-ESMA	4047438011433	30,5 cm	C	148,00	EUR
	In-Ceiling Set Q2x/D2x/ExtIO, Stainless Steel Matt	90079100	23,5 cm			
	Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (matt) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm	724 g	12,0 cm			
	MX-OPT-IC-ESPO	4047438011426	30,5 cm	C	148,00	EUR
	In-Ceiling Set Q2x/D2x/ExtIO, Stainless Steel Polished	90079100	23,5 cm			
	Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (polished) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm	724 g	12,0 cm			
	MX-OPT-IC	4047438011365	30,5 cm	C	98,00	EUR
	In-Ceiling Set For Q2x/D2x/ExtIO, White	90079100	23,5 cm			
	Suitable for: Q2x, D2x, ExtIO • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm	550 g	16,0 cm			

**MX-OPT-TW-Demo-1****table-/wall-mount for demo purposes**

Useful mount for testing and for finding the optimum mounting position of the single lens cameras Q2x Hemispheric or D2x Dome. The set includes an Allen wrench and a Torx screw with dowel and the corresponding Torx wrench for installing as alternative wall mount for testing. The camera can be placed on a flat surface or can be mounted on a tripod (1/4" tripod thread at the bottom of the mount).

4047438013055	21,0 cm	C	28,00	EUR
90079100	8,5 cm			
200 g	8,5 cm			

MOBOTIX Cables

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-FLEX-OPT-CBL-015	4047438019941	13,5 cm	C	10,00 EUR
	Sensor Module Cable For M15, 0.15 m	85444210	8,0 cm		
	Length: 0.15 m/0.5 ft, angled plugs, only for M15 (used inside the housing)	16 g	2,0 cm		
	MX-FLEX-OPT-CBL-05	4047438018890	10,9 cm	C	18,00 EUR
	Sensor Cable For S1x, 0.5 m	85444210	6,5 cm		
	Sensor cable, length 0.5 m/1.6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module (MX-S15D-Sec)	120 g	10,3 cm		
	MX-FLEX-OPT-CBL-1	4047438018883	10,9 cm	C	22,00 EUR
	Sensor Cable For S1x, 1 m	85444210	6,5 cm		
	Sensor cable, length 1 m/3.3 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module (MX-S15D-Sec)	120 g	10,3 cm		
	MX-FLEX-OPT-CBL-2	4047438018876	10,9 cm	C	28,00 EUR
	Sensor Cable For S1x, 2 m	85444210	6,5 cm		
	Sensor cable, length 2 m/6.6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module (MX-S15D-Sec)	120 g	10,3 cm		
	MX-FLEX-OPT-CBL-3	4047438024303	10,9 cm	C	34,00 EUR
	Sensor Cable For S15 (6MP/Thermal), 3 m	85444210	6,5 cm		
	Sensor cable, length 3 m/9.8 ft • For connecting optical sensor modules and BlockFlexMounts with 6MP sensors and Thermal sensor modules to the S15 camera module (MX-S15D-Sec) • Not compatible with PTMount-Thermal, S14D and 5MP modules	130 g	10,3 cm		
	MX-CBL-MU-EN-AB-05	4047438016728	10,3 cm	C	12,00 EUR
	USB Device Cable For M/Q/T25, 0.5 m	85444210	6,5 cm		
	MiniUSB angled > USB-A straight • Length 0.5 m/1.6 ft • For M15, M24/M25, Q24/Q25, T24/T25 • To connect ext. USB device	52 g	10,3 cm		
	MX-CBL-MU-EN-AB-2	4047438016711	10,3 cm	C	15,00 EUR
	USB Device Cable For M/Q/T25, 2 m	85444210	6,5 cm		
	MiniUSB angled > USB-A straight • Length 2 m/6.6 ft • For M15, M24/M25, Q24/Q25, T24/T25 • To connect ext. USB-Gerät	102 g	10,3 cm		


	MX-CBL-MU-EN-AB-5	4047438016704	10,3 cm	C	18,00	EUR
	USB Device Cable For M/Q/T25, 5 m	85444210	6,5 cm			
	MiniUSB angled > USB-A straight • Length 5 m/16,4 ft • For M15, M24/M25, Q24/Q25, T24/T25 • To connect ext. USB device	194 g	10,3 cm			
	MX-CBL-MU-EN-EN-PG-05	4047438020947	10,3 cm	C	12,00	EUR
	ExtIO Cable For M/Q/T25, 0,5 m	85444210	6,5 cm			
	MiniUSB angled > MiniUSB+ angled • Length 0,5 m/1,6 ft • For M15, M24/M25, Q24/Q25, T24/T25 • To connect MX-ExtIO	52 g	10,3 cm			
	MX-CBL-MU-EN-EN-PG-2	4047438020930	10,3 cm	C	15,00	EUR
	ExtIO Cable For M/Q/T25, 2 m	85444210	6,5 cm			
	MiniUSB angled > MiniUSB+ angled • Length 2 m/6,6 ft • For M15, M24/M25, Q24/Q25, T24/T25 • To connect MX-ExtIO	102 g	10,3 cm			
	MX-CBL-MU-EN-EN-PG-5	4047438020923	10,3 cm	C	18,00	EUR
	ExtIO Cable for M/Q/T25, 5 m	85444210	6,5 cm			
	MiniUSB angled > MiniUSB+ angled • Length 5 m/16,4 ft • For M15, M24/M25, Q24/Q25, T24/T25 • To connect MX-ExtIO	194 g	10,3 cm			
	MX-CBL-MU-EN-PG-AB-05	4047438020916	10,3 cm	C	12,00	EUR
	USB Device Cable For D25, 0,5 m	85444210	6,5 cm			
	MiniUSB+ angled > USB-A straight • Length 0,5 m/1,6 ft • For D24/D25 • To connect ext. USB device	52 g	10,3 cm			
	MX-CBL-MU-EN-PG-AB-2	4047438020909	10,3 cm	C	15,00	EUR
	USB Device Cable For D25, 2 m	85444210	6,5 cm			
	MiniUSB+ angled > USB-A straight • Length 2 m/6,6 ft • For D24/D25 • to connect ext. USB device	102 g	10,3 cm			
	MX-CBL-MU-EN-PG-AB-5	4047438020893	10,3 cm	C	18,00	EUR
	USB Device Cable For D25, 5 m	85444210	6,5 cm			
	MiniUSB+ angled > USB-A straight • Length 5 m/16,4 ft • For D24/D25 • To connect ext. USB device	194 g	10,3 cm			
	MX-CBL-MU-EN-PG-EN-PG-05	4047438020886	10,3 cm	C	12,00	EUR
	ExtIO Cable For D25, 0,5 m	85444210	6,5 cm			
	MiniUSB+ angled > MiniUSB+ angled • Length 0,5 m/1,6 ft • For D24/D25 • To connect MX-ExtIO	52 g	10,3 cm			

	MX-CBL-MU-EN-PG-EN-PG-2 ExtIO Cable For D25, 2 m MiniUSB+ angled > MiniUSB+ angled • Length 2 m/6,6 ft • For D24/D25 • To connect MX-ExtIO	4047438020879 85444210 102 g	10,3 cm 6,5 cm 10,3 cm	C	15,00 EUR
	MX-CBL-MU-EN-PG-EN-PG-5 ExtIO Cable For D25, 5 m MiniUSB+ angled > MiniUSB+ angled • Length 5 m/16,4 ft • For D24/D25 • To connect MX-ExtIO	4047438020862 85444210 194 g	10,3 cm 6,5 cm 10,3 cm	C	18,00 EUR
	MX-CBL-MU-EN-PG-STR-05 232-IO-Box Cable For D25, 0.5 m MiniUSB+ angled > MiniUSB straight • Length 0,5 m/1,6 ft • For D24/D25 • To connect MX-232-IO-Box	4047438020855 85444210 52 g	10,3 cm 6,5 cm 10,3 cm	C	12,00 EUR
	MX-CBL-MU-EN-PG-STR-2 232-IO-Box Cable For D25, 2 m MiniUSB+ angled > MiniUSB straight • Length 2 m/6,6 ft • For D24/D25 • To connect MX-232-IO-Box	4047438020848 85444210 102 g	10,3 cm 6,5 cm 10,3 cm	C	15,00 EUR
	MX-CBL-MU-EN-PG-STR-5 232-IO-Box Cable For D25, 5 m MiniUSB+ angled > MiniUSB straight • Length 5 m/16,4 ft • For D24/D25 • To connect MX-232-IO-Box	4047438020831 85444210 194 g	10,3 cm 6,5 cm 10,3 cm	C	18,00 EUR
	MX-CBL-MU-EN-STR-05 232-IO-Box Cable For M/Q/T25, 0.5 m MiniUSB angled > MiniUSB straight • Length 0,5 m/1,6 ft • For M15, M24/M25, Q24/Q25, T24/T25 • To connect MX-232-IO-Box	4047438016667 85444210 52 g	10,3 cm 6,5 cm 10,3 cm	C	12,00 EUR
	MX-CBL-MU-EN-STR-2 232-IO-Box Cable For M/Q/T25, 2 m MiniUSB angled > MiniUSB straight • Length 2 m/6,6 ft • For M15, M24/M25, Q24/Q25, T24/T25 • To connect MX-232-IO-Box	4047438016650 85444210 102 g	10,3 cm 6,5 cm 10,3 cm	C	15,00 EUR
	MX-CBL-MU-EN-STR-5 232-IO-Box Cable For M/Q/T25, 5 m MiniUSB angled > MiniUSB straight • Length 5 m/16,4 ft • For M15, M24/M25, Q24/Q25, T24/T25 • To connect MX-232-IO-Box	4047438016643 85444210 194 g	10,3 cm 6,5 cm 10,3 cm	C	18,00 EUR

	MX-CBL-MU-STR-05 232-IO-Box Cable For D/S/V15, 0.5 m MiniUSB straight > MiniUSB straight • Length 0,5 m/1,6 ft • For D14/D15, S14/S15, V14/V15 • To connect MX-232-IO-Box	4047438016605 85444210 52 g	10,3 cm 6,5 cm 10,3 cm	C	12,00 EUR
	MX-CBL-MU-STR-2 232-IO-Box Cable For D/S/V15, 2 m MiniUSB straight > MiniUSB straight • Length 2 m/6,6 ft • For D14/D15, S14/S15, V14/V15 • To connect MX-232-IO-Box	4047438016599 85444210 102 g	10,3 cm 6,5 cm 10,3 cm	C	15,00 EUR
	MX-CBL-MU-STR-5 232-IO-Box Cable For D/S/V15, 5 m MiniUSB straight > MiniUSB straight • Length 5 m/16,4 ft • For D14/D15, S14/S15, V14/V15 • To connect MX-232-IO-Box	4047438016445 85444210 196 g	10,3 cm 6,5 cm 10,3 cm	C	18,00 EUR
	MX-CBL-MU-STR-AB-05 USB Device Cable For D/S/V15, 0.5 m MiniUSB straight > USB-A straight • Length 0,5 m/1,6 ft • For D14/D15, S14/S15, V14/V15 • To connect ext. USB device	4047438016698 85444210 52 g	10,3 cm 6,5 cm 10,3 cm	C	12,00 EUR
	MX-CBL-MU-STR-AB-2 USB Device Cable For D/S/V15, 2 m MiniUSB straight > USB-A straight • Length 2 m/6,6 ft • For D14/D15, S14/S15, V14/V15 • To connect ext. USB device	4047438016681 85444210 102 g	10,3 cm 6,5 cm 10,3 cm	C	15,00 EUR
	MX-CBL-MU-STR-AB-5 USB Device Cable For D/S/V15, 5 m MiniUSB straight > USB-A straight • Length 5 m/16,4 ft • For D14/D15, S14/S15, V14/V15 • To connect ext. USB device	4047438016674 85444210 194 g	10,3 cm 6,5 cm 10,3 cm	C	18,00 EUR
	MX-CBL-MU-STR-EN-PG-05 ExtIO Cable For D/S/V15, 0.5 m MiniUSB straight > MiniUSB+ angled • Length 0,5 m/1,6 ft • For D14/D15, S14/S15, V14/V15 • To connect MX-ExtIO	4047438020978 85444210 52 g	10,3 cm 6,5 cm 10,3 cm	C	12,00 EUR
	MX-CBL-MU-STR-EN-PG-2 ExtIO Cable For D/S/V15, 2 m MiniUSB straight > MiniUSB+ angled • Length 2 m/6,6 ft • For D14/D15, S14/S15, V14/V15 • To connect MX-ExtIO	4047438020961 85444210 102 g	10,3 cm 6,5 cm 10,3 cm	C	15,00 EUR

	MX-CBL-MU-STR-EN-PG-5 ExtIO Cable For D/S/V15, 5 m MiniUSB straight > MiniUSB+ angled • Length 5 m/16,4 ft • For D14/D15, S14/S15, V14/V15 • To connect MX-ExtIO	4047438020954 85444210 194 g	10,3 cm 6,5 cm 10,3 cm	C	18,00 EUR
	MX-OPT-CBL-LAN-1 Ethernet Patch Cable, 1 m Ethernet Patch Cable for MOBOTIX systems • Length 1 m/3,3 ft • 2x RJ45 plug with special MOBOTIX sealing ring	4047438012300 85444210 36 g	23,5 cm 15,0 cm 2,0 cm	C	8,00 EUR
	MX-OPT-CBL-LAN-10 Ethernet Patch Cable, 10 m Ethernet Patch Cable for MOBOTIX systems • Length 10 m/32,8 ft • 2x RJ45 plug with special MOBOTIX sealing ring	4047438012331 85444210 264 g	27,0 cm 17,0 cm 4,0 cm	C	28,00 EUR
	MX-OPT-CBL-LAN-2 Ethernet Patch Cable, 2 m Ethernet Patch Cable for MOBOTIX systems • Length 2 m/6,6 ft • 2x RJ45 plug with special MOBOTIX sealing ring	4047438012317 85444210 62 g	23,5 cm 15,0 cm 2,0 cm	C	12,00 EUR
	MX-OPT-CBL-LAN-5 Ethernet Patch Cable, 5 m Ethernet Patch Cable for MOBOTIX systems • Length 5 m/16,4 ft • 2x RJ45 plug with special MOBOTIX sealing ring	4047438012324 85444210 144 g	23,5 cm 15,0 cm 4,0 cm	C	18,00 EUR
	MX-FLEX-IO-CBL-015 IO Connection Cable For M15, 0.15 m Length: 0.15 m/0,5 ft, IO cable to the front element of the camera, only for M15 (inside camera housing)	4047438019958 85444210 10 g	13,5 cm 8,0 cm 2,0 cm	C	6,00 EUR
	MX-CBL-NPA-BAT-2 NPA Battery Cable, 2 m NPA-PoE Battery Cable • Provides a power supply for the camera from car batteries or other power sources from 12 to 24 Volts • With self-resetting fuse • RJ45 connector to PoE injector, „+/-“ terminals for power source • Can only be used with Mx-NPA PoE injector • Length: 2 m/6.6 ft	4047438013949 85444210 54 g	10,5 cm 5,0 cm 8,5 cm	C	24,00 EUR

Other Camera Accessories

Article No. / Name / Description	EAN / HS / weight	dimen. DG	MSRP
	MX-OPT-Ring-L10-L12-BL Sealing Ring For Hemispheric Sensor Modules, Black Enables weather resistance when removing the plastic dome of black hemispheric sensor modules (S15/M15) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: black	4047438021241 8,5 cm C 90079100 6,0 cm 16 g 3,5 cm	2,00 EUR
	MX-OPT-Ring-L10-L12-PW Sealing Ring For Hemispheric Sensor Modules, White Enables weather resistance when removing the plastic dome of white hemispheric sensor modules (S15/M15) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: white	4047438021234 8,5 cm C 90079100 6,0 cm 16 g 3,5 cm	2,00 EUR
	MX-OPT-SEC-SCREWS-SET Security Screw Set With Allen Bit For M15/M25 Triple set of anti-theft screws for plugs (4 pcs 6x50) and for machine threads (4 pcs M6x15, 4 pcs M6x30) to securely attach the VarioFlex wall mount • incl. Allen bit for power screwdrivers (1/4" in drive with hole for security pin)	4047438021265 8,5 cm C 90079100 6,0 cm 120 g 3,5 cm	12,00 EUR
	MX-SM-Blind-PW Blind Module M15 For M15 and M15 Thermal • When operating the camera, it needs to be fitted either with sensor or blind modules. This closes off the front element and protects the camera against foreign objects, insects and water.	4047438019965 9,0 cm C 90079100 6,0 cm 38 g 4,0 cm	4,00 EUR



System Components

All prices are Manufacturer's suggested retail prices, net, ex works. Information subject to change without notice.
HS = Harmonized System Code DG = Discount Group

Interface Boxes

Weatherproof Expansion Of Functions For MOBOTIX Systems.

With the interface boxes, MOBOTIX can provide a full security solution to sense different inputs and operate different outputs or 3rd party devices, like window or door contacts, lamps and motors. All interface boxes are weatherproof, outdoor resistant and can be installed invisible behind the standard camera wall mount, requiring only one installation point. All boxes are managed via the encrypted 2-wire MxBus from the camera, doorstation, MxDisplay+ or the MxManagementCenter.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-OPT-BPA1-EXT	4047438025881	8,5 cm	C	98,00 EUR
	MX-BPA-Box	85299065	10,5 cm		
	Power supply for several MxBus modules of one MxBus line • 2x2 connection terminals for MxBus • 2 connection terminals for external power supply from 12 to 48 V DC (2 terminals) • Max. output rating: 9 W • IP65, -30 bis 60 °C / -22 to 140 °F • Box can be mounted safely out of reach in the wall mounts of M15, M25, D15 and D25	120 g	5,0 cm		
	MX-OPT-GPS1-EXT	4047438015400	8,5 cm	C	178,00 EUR
	MX-GPS-Box	85299065	10,5 cm		
	Weatherproof GPS time base for MOBOTIX systems • Includes outdoor temperature and illumination sensors • Connects via MxBus 2-wire cable • Protection class IP65, -30 to 60°C / -22 to +140°F • Box can be mounted safely out of reach in the wall mounts of M15, M25, D15 and D25	120 g	5,0 cm		
	MX-OPT-Input1-EXT	4047438021227	8,5 cm	C	128,00 EUR
	MX-Input-Box	85299065	10,5 cm		
	Weatherproof connection of external sensors • Connection to camera using MxBus • 6 self-powered inputs for up to 6 connecting sensors • Protection class IP65, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M15, M25, D15 and D25	120 g	5,0 cm		
	MX-OPT-NPA1-EXT	4047438015424	8,5 cm	C	128,00 EUR
	MX-NPA-Box	85043180	10,5 cm		
	Weatherproof PoE Injector (IEEE 802.3af) and network connector • Needs external power supply units and batteries from 12 to 57 V DC • Protection class IP65, -30 to 60°C / -22 to 140°F • Important: only use with original MOBOTIX patch cables • Box can be mounted safely out of reach in the wall mounts of M15, M25, D15 and D25	120 g	5,0 cm		
	MX-OPT-Output1-EXT	4047438021944	8,5 cm	C	128,00 EUR
	MX-Output-Box	85299065	10,5 cm		
	Weatherproof connection of external devices and power relays • Connection to the camera via MxBus • Six self-powered outputs (12 V, each 10 mA) • Two isolated outputs (can be switched to "self-powered" using a jumper: 12 V, max. 50 mA) • Protection class IP65, -30 to 60 °C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M15, M25, D15 and D25	120 g	5,0 cm		
	MX-OPT-RS1-EXT	4047438015417	8,5 cm	C	148,00 EUR
	MX-232-IO-Box	85299065	10,5 cm		
	Weatherproof connection of external sensors and switching of external devices via MOBOTIX cameras • Connection to camera using USB or MxBus • 2 self-powered inputs for connecting sensors • 2 outputs: 1 powered output, 1 isolated relay output (can be switched to second powered output) • RS232 interface when using MOBOTIX USB cable to connect to camera • Protection class IP65, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M15, M25, D15 and D25	120 g	5,0 cm		

**MX-Overvoltage-Protection-Box-LSA****Network Connector with Surge Protection, LSA Version**

Weatherproof connection of one MOBOTIX patch cable (RJ45, from camera) and the network installation cable • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP65, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M15, M25, D15 and D25

4047438018470	8,5 cm	C	48,00	EUR
85299065	10,5 cm			
120 g	5,0 cm			

**MX-Overvoltage-Protection-Box-RJ45****Network Connector with Surge Protection, RJ45 Version**

Weatherproof connection of two MOBOTIX patch cables (RJ45, one from the camera) • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP65, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M15, M25, D15 and D25

4047438018463	8,5 cm	C	48,00	EUR
85299065	10,5 cm			
120 g	5,0 cm			

Mx2wire+ Media Converter

Ethernet & PoE Via Two-Wire Cable.

Using the Mx2wire system from MOBOTIX, an Ethernet network with PoE can be established using existing cables up to 500 m. This means that you can utilize a two-wire cable that is no longer in use (analog telephone line, antenna cable or bell wire, for instance) to connect a 10/100 Mbps Ethernet device such as a PC, WLAN, IP camera, IP telephone or IP door station without having to lay any new cables or implement any other constructional measures. A Mx2wire unit is required at both ends of the cable, and it automatically configures itself as either the sender or the receiver (MOBOTIX patent). The significant additional benefit of Mx2wire is that, in addition to data, the power to operate PoE end devices (Power over Ethernet according to the IEEE 802.3af standard, a MOBOTIX network camera, for example) can also be transferred via the two-wire cable.

Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP	
	MX-2WirePlus-Set-PW	4047438015356	23,0 cm	C	298,00 EUR
	Mx2wire+ Set, Ethernet And PoE Via Two-Wire-Cable	85299065	19,0 cm		
	Mx2wire+ turns an existing two-wire cable into a modern multimedia cable • Ethernet and PoE data transfer using a two-wire cable • Simple connection of 10/100 Mbps Ethernet end devices (e.g., IP camera, IP telephone) • Power supply for Mx2wire+ and end device via PoE/PoE+ or 48–57 V DC, 600 mA • Connected end devices are supplied with up to 13 watts via PoE (PoE class 3) • Maximum data transfer range of 500 m and data rate of up to 50 Mbps (depending on distance) • No need for expensive and time-consuming installation of network cables • Perfect for wireless communication is not possible (due to distance to sender, thickness of walls, etc.) • Network extension, including PoE, by connecting a Cat7 cable of up to 500 m in length as a two-wire cable • Simple installation in standard sockets (surface- or flush-mounted) • Two LEDs display current connection and supply statuses • Developed, produced and patented by MOBOTIX Germany • Ambient temperature: -30 to 50°C / -22 to 122°F • Complete set consisting of two Mx2wire+ units, on-walls sockets and mounting parts	696 g	8,5 cm		

IO Modules

Intercom Device With Sensors And Inputs.

The ExtIO module extends the functionality of your MOBOTIX camera, providing 2-way intercom communication via its in-built microphone and speaker. It also includes a passive infrared motion sensor, a temperature sensor and additional signal inputs/outputs. The two programmable buttons are ideally suited for activating camera functions and external electronic devices. The ExtIO can be connected to a MOBOTIX camera directly via USB or network switch.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-OPT-IO3-INT	4047438025928	10,5 cm	C	78,00 EUR
	Extension Module For i25, c25, p25 and v25	85299065	8,5 cm		
	Extension module for the indoor cameras i25, c25, p25 and v25 (to be mounted on the backside) • For the connection of external sensors (e.g., door or window contacts) and switching of external devices (e.g., relays with lamps and motors) • Two input lines (galvanically isolated, 0 to 48 V AC/DC) • Two output lines: 2x isolated (contact load max.30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA per output line) • MxBus terminal (1x2) • Ambient temperature: 0 to 40°C (32 to 104°F) • Power consumption: 1 W	45 g	5,0 cm		
	MX-ExtIO	4047438009850	31,0 cm	C	198,00 EUR
	ExtIO Extension Module For All MOBOTIX Cameras	85299065	24,0 cm		
	ExtIO Weatherproof extension for all MOBOTIX cameras (except Basic models) • Power supply: PoE (Class 2, IEEE 802.3af) or USB (connection cable to be ordered individually) • Microphone/speaker • Line-in / Line-out • PIR sensor for motion detection • Temperature sensor • 2 buttons (e.g., lights, door bell) • 2 galvanically separated inputs • 2 galvanically separated outputs • Protection class IP65, -30 to 60°C / -22 to 140°F • Robust housing made of fiber-reinforced plastic PBT-GF30 • Mounting to a wall or ceiling, optionally with MOBOTIX mounting accessories (to be ordered individually) • Connecting via Network or USB	1.158 g	16,0 cm		

NPA PoE Set

Green IP Video. By MOBOTIX.

The modern, network-based video security technology offers numerous advantages to use energy efficiently. Due to the special product and system properties, the decision to install MOBOTIX video systems is also a decision for Green IP Video: low power consumption and environmental friendly because of long life expectancy and minimal amount of materials involved.

Since all MOBOTIX cameras neither fog up nor require heating, power can be supplied very cost-efficiently via the network cabling using standardized PoE products. This reduces the expenses for power and, in addition, saves copper and other important raw material as less power cabling is necessary.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-NPA-PoE-EU-Set	4047438012249	16,0 cm	C	98,00 EUR
	PoE Power Adapter Set, EU	85043180	10,0 cm		
	PoE injector incl. crossover function for direct connection to the PC • With power plug for Europe • For all MOBOTIX cameras (except for M1 und M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug	256 g	5,5 cm		
	MX-NPA-PoE-INT-Set	4047438012256	16,0 cm	C	98,00 EUR
	PoE Power Adapter Set, INT	85043180	10,0 cm		
	PoE injector incl. crossover function for direct connection to the PC • With 4 exchangeable power plugs for Europe, United Kingdom, USA and Australia • For all MOBOTIX cameras (except for M1 und M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug	256 g	5,5 cm		
	MX-NPA-PoE-RJ	4047438013932	10,5 cm	C	78,00 EUR
	PoE Power Adapter	85043180	9,0 cm		
	PoE injector (IEEE 802.3af) incl. crossover function for direct connection to the PC • Blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug • Without power plug, additional power supply (12 to 57 V DC) and connection cable needed	90 g	5,0 cm		
	MX-SNT-INT-PoE	4047438013925	10,5 cm	C	48,00 EUR
	Universal Power Supply With 4 Power Plugs	85043180	9,0 cm		
	For international use thanks to broad input voltage range and interchangeable power plugs (no tools required) • With 4 power plugs for Europe, United Kingdom, USA and Australia • Connections: 1x RJ45 (for adapter), 1x network (up to 4x interchangeable adapter) • Nominal data input: 100 V to 240 V, 50 to 60 Hz/400 mA • Nominal data output: DC 24 V/750 mA • Ambient temperature: 0 to 40°C / 32 to 104 °F	160 g	5,0 cm		



Building Automation

All prices are Manufacturer's suggested retail prices, net, ex works. Information subject to change without notice.
HS = Harmonized System Code DG = Discount Group

MxDisplay+

The "Smartphone" On The Wall.

The MOBOTIX Display+ is much more than an intercom system or a simple display of a door station. It is a building automation server and supports access to security cameras, manages the time based access control for each door, reads and writes RFID transponders, controls smart home functions and acts as a standard house alarm system with several lines. The MOBOTIX MxDisplay+ supports gesture control like a smartphone and therefore it is very user friendly and intuitive in use.

The access control can be defined individually by groups, users and doors. Beside using RFID batches or transponder tags, also pin numbers for access control can be defined or the combination of transponder and pin code is supported. For example it takes approx. 10 seconds to set up an entry code or transponder batch for a craftsman. The entry or access time can be set by time range or is defined by detailed weekly schedule. Access codes are encrypted and therefore reliable and safe.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-DISPLAY3	4047438027151	14,7 cm	C	698,00 EUR
	MxDisplay+, White	85285931	13,7 cm		
	MxDisplay+ with second generation CPU • Indoor remote station for MOBOTIX Door Stations and video systems • Full duplex hands-free talking, HD sound with echo/noise suppression and automatic volume control • Ambilight sensor • 3 inputs, 1 relay output, connection for external temperature sensor and MxBus (MxMessageSystem) • Ethernet, RFID and Wi-Fi • 1 x admin card • Mounting parts • Frame and in-wall housing can be ordered separately (for example, FlatMount Frame MX-OPT-FlatMount-EXT-PW) • Color: white	270 g	5,5 cm		
	MX-DISPLAY3-b	4047438027168	14,7 cm	C	698,00 EUR
	MxDisplay+, Black	85285931	13,7 cm		
	MxDisplay+ with second generation CPU • Indoor remote station for MOBOTIX Door Stations and video systems • Full duplex hands-free talking, HD sound with echo/noise suppression and automatic volume control • Ambilight sensor • 3 inputs, 1 relay output, connection for external temperature sensor and MxBus (MxMessageSystem) • Ethernet, RFID and Wi-Fi • 1 x admin card • Mounting parts • Frame and in-wall housing can be ordered separately (for example, FlatMount Frame MX-OPT-FlatMount-EXT-BL) • Color: black	270 g	5,5 cm		

T25 Complete Kits

Better Overview. Increased Security. More Possibilities.

The IP Video Door Station from MOBOTIX is an innovative, modular system for door communication and access control. The system supports the VoIP/SIP video telephony standard and can be upgraded or modified at any time. The camera module records all events taking place in front of the building or gate; when the bell is pushed, when motion is detected in the image area or upon triggering a contact. Fit for any weather, at dawn and dusk, as well as for backlight situations.

The camera module with a remote station can be used as a compact basic video door station thanks to the integrated doorbell and light buttons. The camera saves high-resolution video with lip-synchronous sound directly to the integrated 4 GB microSD card without requiring an external storage device or computer and with no additional network load.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-T25-SET1	4047438025362	34,0 cm	C	1.298,00 EUR
	T25 6MP Set 1, Ethernet, Keypad, White	85258091	34,0 cm		
	Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: White	3.000 g	16,0 cm		
	MX-T25-SET2	4047438025379	34,0 cm	C	1.838,00 EUR
	T25 6MP Set 2, Two-Wire, Keypad, DoorMaster, White	85258091	34,0 cm		
	Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info2Wire+ (Info Module with indoor unit) • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: White	3.000 g	16,0 cm		
	MX-T25-SET3	4047438025386	34,0 cm	C	1.538,00 EUR
	T25 6MP Set 3, Ethernet, Keypad, DoorMaster, White	85258091	34,0 cm		
	Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: White	3.000 g	16,0 cm		

T25 Complete Kits (SUP)

Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. These kits can also be ordered from the standard program as individual components for self-assembly.

Please note: Black colored IP Video Door Stations should NOT be exposed to direct sunlight (risk of overheating on dark surfaces).

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-T25-SET1-s	4047438025607	34,0 cm	C	1.298,00 EUR
	T25 6MP Set 1, Ethernet, Keypad, Silver	85258091	34,0 cm		
	Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Silver	3.000 g	16,0 cm		
	MX-T25-SET1-b	4047438025447	34,0 cm	C	1.298,00 EUR
	T25 6MP Set 1, Ethernet, Keypad, Black	85258091	34,0 cm		
	Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Black	3.000 g	16,0 cm		
	MX-T25-SET2-s	4047438025614	34,0 cm	C	1.838,00 EUR
	T25 6MP Set 2, Two-Wire, Keypad, DoorMaster, Silver	85258091	34,0 cm		
	Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info2wire+ (Info Module with indoor unit) • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Silver	3.000 g	16,0 cm		
	MX-T25-SET2-b	4047438025454	34,0 cm	C	1.838,00 EUR
	T25 6MP Set 2, Two-Wire, Keypad, DoorMaster, Black	85258091	34,0 cm		
	Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info2wire+ (Info Module with indoor unit) • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Black	3.000 g	16,0 cm		
	MX-T25-SET3-s	4047438025621	34,0 cm	C	1.538,00 EUR
	T25 6MP Set 3, Ethernet, Keypad, DoorMaster, Silver	85258091	34,0 cm		
	Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Silver	3.000 g	16,0 cm		
	MX-T25-SET3-b	4047438025461	34,0 cm	C	1.538,00 EUR
	T25 6MP Set 3, Ethernet, Keypad, DoorMaster, Black	85258091	34,0 cm		
	Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Black	3.000 g	16,0 cm		

T25 Camera Module

The World's Most Advanced Door Station.

With a 180° field of view, the T25 camera module captures everything wall-to-wall. Includes programmable buttons for activating lights and a bell. Hemispheric image correction is handled by the camera, no additional software required. Built-in VoIP/SIP for instant 2-way communication via PC or mobile device.

Please note: Black, dark gray and amber colored IP Video Door Stations should NOT be exposed to direct sunlight (risk of overheating on dark surfaces).

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-T25-D016	4047438025263	30,5 cm	C	798,00 EUR
	CamCore T25, 6MP, 1.6 mm, Day, White	85258091	23,5 cm		
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White	1.240 g	11,5 cm		
	MX-T25-D016-s	4047438025270	30,5 cm	C	798,00 EUR
	CamCore T25, 6MP, 1.6 mm, Day, Silver	85258091	23,5 cm		
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver	1.240 g	11,5 cm		
	MX-T25-D016-b	4047438025300	30,5 cm	C	798,00 EUR
	CamCore T25, 6MP, 1.6 mm, Day, Black	85258091	23,5 cm		
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Black	1.240 g	11,5 cm		
	MX-T25-N016	4047438025317	30,5 cm	C	798,00 EUR
	CamCore T25, 6MP, 1.6 mm, Night, White	85258091	23,5 cm		
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White	1.240 g	11,5 cm		
	MX-T25-N016-s	4047438025324	30,5 cm	C	798,00 EUR
	CamCore T25, 6MP, 1.6 mm, Night, Silver	85258091	23,5 cm		
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver	1.240 g	11,5 cm		
	MX-T25-N016-b	4047438025355	30,5 cm	C	798,00 EUR
	CamCore T25, 6MP, 1.6 mm, Night, Black	85258091	23,5 cm		
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Black	1.240 g	11,5 cm		

	MX-T25M-Sec-D12-PW	4047438019972	30,5 cm	C	748,00	EUR
	CamCore T25, 5MP, Hemispheric L12 (Day), White	85258091	23,5 cm			
	IP door station camera module (illuminated) with image sensor and fisheye lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L12 Hemispheric (horizontal image angle 180°) • Equipment line: Secure • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White	1.240 g	11,5 cm			
	MX-T25M-Sec-D12-SV	4047438019989	30,5 cm	C	748,00	EUR
	CamCore T25, 5MP, Hemispheric L12 (Day), Silver	85258091	23,5 cm			
	IP door station camera module (illuminated) with image sensor and fisheye lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L12 Hemispheric (horizontal image angle 180°) • Equipment line: Secure • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver	1.240 g	11,5 cm			
	MX-T25M-Sec-D12-BL	4047438020008	30,5 cm	C	748,00	EUR
	CamCore T25, 5MP, Hemispheric L12 (Day), Black	85258091	23,5 cm			
	IP door station camera module (illuminated) with image sensor and fisheye lens • Image sensor: 1/2.5" CMOS, 5 megapixels, color (day) • Lens: L12 Hemispheric (horizontal image angle 180°) • Equipment line: Secure • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Black	1.240 g	11,5 cm			
	MX-T25M-Sec-Night-N12-PW	4047438020022	30,5 cm	C	748,00	EUR
	CamCore T25, 5MP, Hemispheric L12 (Night), Pure White	85258091	23,5 cm			
	IP door station camera module (illuminated) with image sensor and fisheye lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L12 Hemispheric (horizontal image angle 180°) • Equipment line: Secure • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White	1.240 g	11,5 cm			
	MX-T25M-Sec-Night-N12-SV	4047438020039	30,5 cm	C	748,00	EUR
	CamCore T25, 5MP, Hemispheric L12 (Night), Silver	85258091	23,5 cm			
	IP door station camera module (illuminated) with image sensor and fisheye lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L12 Hemispheric (horizontal image angle 180°) • Equipment line: Secure • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver	1.240 g	11,5 cm			
	MX-T25M-Sec-Night-N12-BL	4047438020053	30,5 cm	C	748,00	EUR
	CamCore T25, 5MP, Hemispheric L12 (Night), Black	85258091	23,5 cm			
	IP door station camera module (illuminated) with image sensor and fisheye lens • Image sensor: 1/2.5" CMOS, 5 megapixels, B/W (night) • Lens: L12 Hemispheric (horizontal image angle 180°) • Equipment line: Secure • Max. image size: 5MP (2592 x 1944 pixels) • Operating conditions: IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB MicroSD • System components: two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Black	1.240 g	11,5 cm			

BellRFID Module

Modular Doorbell System With RFID.

The weatherproof BellRFID module provides keyless entry, voice mailbox control and is available with any one of six available bell button sets. The bell button sets are customizable and can be exchanged at any time. The module allows visitors to record messages, which residences can play back locally or remotely. Includes mailbox feature, 1x admin and 5x user RFID cards.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-Bell1-Button-F1	4047438017190	10,5 cm	C	28,00 EUR
	BellRFID Bell Button Set F1	85299065	10,3 cm		
	1 big key with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label	94 g	1,6 cm		
	MX-Bell1-Button-F2	4047438017176	10,5 cm	C	28,00 EUR
	BellRFID Bell Button Set F2	85299065	10,3 cm		
	2 medium-sized keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label	94 g	1,6 cm		
	MX-Bell1-Button-F3	4047438017527	10,5 cm	C	28,00 EUR
	BellRFID Bell Button Set F3	85299065	10,3 cm		
	1 medium-sized and 2 small keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label •	94 g	1,6 cm		
	MX-Bell1-Button-F4	4047438017183	10,5 cm	C	28,00 EUR
	BellRFID Bell Button Set F4	85299065	10,3 cm		
	4 small keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label	94 g	1,6 cm		
	MX-Bell1-Button-05	4047438017534	10,5 cm	C	28,00 EUR
	BellRFID Bell Button Set 05	85299065	10,3 cm		
	5 small keys (without blue functional bar) • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label	94 g	1,6 cm		
	MX-Bell1-Button-XL1	4047438017169	10,5 cm	C	28,00 EUR
	BellRFID Bell Button Set XL1	85299065	10,3 cm		
	1 big XL key (without blue functional bar) • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: www.mobotix.com > Support • Delivery with UV resistant paper label	94 g	1,6 cm		
	MX-Bell1-Core-EXT-PW	4047438017152	10,5 cm	C	270,00 EUR
	BellRFID Base Module, White	85299065	10,3 cm		
	BellRFID access module for MOBOTIX IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	256 g	6,5 cm		

**MX-Bell1-Core-EXT-SV****BellRFID Base Module, Silver**

BellRFID access module for MOBOTIX IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrierte RFID-Technik für schlüssellosen Zutritt • Stromversorgung über die Türkamera via Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver

4047438017114	10,5 cm	C	270,00	EUR
85299065	10,3 cm			
256 g	6,5 cm			

**MX-Bell1-Core-EXT-BL****BellRFID Base Module, Black**

BellRFID access module for MOBOTIX IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black

4047438017145	10,5 cm	C	270,00	EUR
85299065	10,3 cm			
256 g	6,5 cm			

KeypadRFID Module

Keyless And Scheduled Access.

The weatherproof KeypadRFID module provides keyless entry and voice mailbox control. The modules allow visitors to record messages, which residences can play back locally or remotely. Includes 1x admin and 5x user RFID cards.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-Keypad1-EXT-PW	4047438014946	10,0 cm	C	298,00 EUR
	Keypad With RFID Technology, White	85371091	6,5 cm		
	Keypad access module for MOBOTIX IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	210 g	10,0 cm		
	MX-Keypad1-EXT-SV	4047438014984	10,0 cm	C	298,00 EUR
	Keypad With RFID Technology, Silver	85371091	6,5 cm		
	Keypad access module for MOBOTIX IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrierte RFID-Technik für schlüssellosen Zutritt • Stromversorgung über die Türkamera via Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver	210 g	10,0 cm		
	MX-Keypad1-EXT-BL	4047438014960	10,0 cm	C	298,00 EUR
	Keypad With RFID Technology, Black	85371091	6,5 cm		
	Keypad access module for MOBOTIX IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black	210 g	10,0 cm		

Info Module

Weatherproof Backlit Display.

Provides the option to attach the house number and/or name to the door station. The module is equipped with permanent backlighting using energy-saving and long-lasting LED technology.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-Info1-EXT-PW	4047438014991	11,0 cm	C	98,00 EUR
	Info Module With LEDs, White	85414090	10,0 cm		
	Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	193 g	6,5 cm		
	MX-Info1-EXT-SV	4047438015035	11,0 cm	C	98,00 EUR
	Info Module With LEDs, Silver	85414090	10,0 cm		
	Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver	193 g	6,5 cm		
	MX-Info1-EXT-BL	4047438015011	11,0 cm	C	98,00 EUR
	Info Module With LEDs, Black	85414090	10,0 cm		
	Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black	193 g	6,5 cm		

Info Module Mx2Wire+

Door Station Installation Via 2-Wire Cable.

The info module with Mx2wire+ technology and a second Mx2wire unit for mounting inside the building offers users not only the standard info module functions but also the option to connect and supply power to the door station via two-wire cabling instead of a network cable.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-2wirePlus-Info1-EXT-PW	4047438015042	23,0 cm	C	448,00 EUR
	Info Module Mx2wire+ With LEDs, White	85176200	19,0 cm		
	Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	626 g	8,5 cm		
	MX-2wirePlus-Info1-EXT-SV	4047438015080	23,0 cm	C	448,00 EUR
	Info Module Mx2wire+ With LEDs, Silver	85176200	19,0 cm		
	Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver	626 g	8,5 cm		
	MX-2wirePlus-Info1-EXT-BL	4047438015066	23,0 cm	C	448,00 EUR
	Info Module Mx2wire+ With LEDs, Black	85176200	19,0 cm		
	Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black	626 g	8,5 cm		

MX-DoorMaster

The Original MOBOTIX Security Door Opener.


This internal security door opener includes door access battery backup and encrypted security for the door access codes, to prevent unauthorized access. Compatible with standard door openers using an external power supply.



	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-Door2-INT-ON-PW	4047438021876	21,0 cm	C	248,00 EUR
	DoorMaster For On-Wall Mounting	85363010	8,5 cm		
	Security Door Opener with integrated access code memory for on-wall mounting • Complete set including DoorMaster module, on-wall housing, three device frames, neutral housing covering, battery pack and mounting parts • Suitable for: IP Video Door Station with T2x and S1x as door camera • Built-in backup power supply (battery) for access modules • Doorbell • Direct connection and power supply for electric Door Opener und door sensors • Interface und power supply: MxBus • Two status LEDs, two function buttons, integrated • Speaker (doorbell) • Two galvanically separated inputs (AC/DC, selfpowered • up to 48 V) • Isolated relay output (AC/DC, 24 V/1 A) or port for standard door openers (6 to 12 V AC) • Outlet for MOBOTIX antitheft protection (12 V DC) • Protection class: IP20 • Ambient temperature: -5 to 40 °C / 23 to 104 °F • Color: white	420 g	8,5 cm		
	MX-Door2-INT-PW	4047438019934	21,0 cm	C	248,00 EUR
	DoorMaster For In-Wall Mounting	85363010	8,5 cm		
	Security door opener with internal access code memory: A MOBOTIX door station may be coupled with the MOBOTIX MX-DoorMaster, making it impossible to open the door by forcibly removing the system and bypassing the connecting cable • 2nd product generation, suitable for: IP video door stations with an T2x and S1x as door camera • Integrated (rechargeable) battery power supply for access modules • Security door opener/bell with access code storage (protected against manipulation) • Connection for door opener, door sensor and door lock sensor • Interface and power supply: MxBus (max. 50 m distance to door station) • User interfaces: 2 status LEDs, 2 function buttons, integrated speaker (doorbell) • Inputs: 2 galvanically separated inputs with shared ground connection (AC/DC, self-powered up to 48 V) • Outputs: 1 isolated relay output (AC/DC, 24 V/1 A) or 1 connector for standard door opener (6 to 12 V AC), 1 output for MOBOTIX theft protection (12 V DC) • Protection class: IP20 (DIN EN 60529) • Operating temperature: -5 to 40°C / 23 to 104°F (DIN EN 50155) • Switch time: max. 5 s	340 g	8,5 cm		



Frames & Housings



For On-Wall And In-Wall Mounting.

All of the door station modules require a frame and housing for the purpose of wall mounting. Frames are available for in-wall and on-wall mounting. Includes unique anti-theft system for device security.

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-OPT-Frame-1-EXT-PW	4047438014892	13,5 cm	C	58,00 EUR
	Single Frame, White	90079100	14,5 cm		
	Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: White	268 g	5,5 cm		
	MX-OPT-Frame-1-EXT-SV	4047438014939	13,5 cm	C	58,00 EUR
	Single Frame, Silver	90079100	14,5 cm		
	Suitable for: 1 module, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Silver	268 g	5,5 cm		
	MX-OPT-Frame-1-EXT-BL	4047438014915	13,5 cm	C	58,00 EUR
	Single Frame, Black	90079100	14,5 cm		
	Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Black	268 g	5,5 cm		
	MX-OPT-Box-1-EXT-ON-PW	4047438015202	14,5 cm	C	48,00 EUR
	Single On-Wall-Housing, White	90079100	13,5 cm		
	Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: White	286 g	5,0 cm		
	MX-OPT-Box-1-EXT-ON-SV	4047438015240	14,5 cm	C	48,00 EUR
	Single On-Wall-Housing, Silver	90079100	13,5 cm		
	Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Silver	286 g	5,0 cm		
	MX-OPT-Box-1-EXT-ON-BL	4047438015226	14,5 cm	C	48,00 EUR
	Single On-Wall-Housing, Black	90079100	13,5 cm		
	Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Black	286 g	5,0 cm		
	MX-OPT-Box-1-EXT-IN	4047438015271	14,5 cm	C	18,00 EUR
	Single In-Wall-Housing	90079100	13,5 cm		
	Suitable for: 1 module, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 129 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	186 g	5,0 cm		

	MX-OPT-Frame-2-EXT-PW	4047438014847	23,5 cm	C	78,00	EUR
	Double Frame, White	90079100	13,5 cm			
	Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: White	333 g	5,0 cm			
	MX-OPT-Frame-2-EXT-SV	4047438014885	23,5 cm	C	78,00	EUR
	Double Frame, Silver	90079100	13,5 cm			
	Suitable for: 2 modules, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Silver	333 g	5,0 cm			
	MX-OPT-Frame-2-EXT-BL	4047438014861	23,5 cm	C	78,00	EUR
	Double Frame, Black	90079100	13,5 cm			
	Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Black	333 g	5,0 cm			
	MX-OPT-Box-2-EXT-ON-PW	4047438015158	23,5 cm	C	58,00	EUR
	Double On-Wall-Housing, White	90079100	13,5 cm			
	Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: White	430 g	3,0 cm			
	MX-OPT-Box-2-EXT-ON-SV	4047438015196	23,5 cm	C	58,00	EUR
	Double On-Wall-Housing, Silver	90079100	13,5 cm			
	Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Silver	430 g	3,0 cm			
	MX-OPT-Box-2-EXT-ON-BL	4047438015172	23,5 cm	C	58,00	EUR
	Double On-Wall-Housing, Black	90079100	13,5 cm			
	Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Black	430 g	3,0 cm			
	MX-OPT-Box-2-EXT-IN	4047438015264	23,5 cm	C	24,00	EUR
	Double In-Wall-Housing	90079100	13,5 cm			
	Suitable for: 2 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 218 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	270 g	5,0 cm			
	MX-OPT-Frame-3-EXT-PW	4047438014793	33,5 cm	C	98,00	EUR
	Triple Frame, White	90079100	13,5 cm			
	Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: White	426 g	5,0 cm			

	MX-OPT-Frame-3-EXT-SV	4047438014830	33,5 cm	C	98,00	EUR
	Triple Frame, Silver	90079100	13,5 cm			
	Suitable for: 3 modules, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Silver	426 g	5,0 cm			
	MX-OPT-Frame-3-EXT-BL	4047438014816	33,5 cm	C	98,00	EUR
	Triple Frame, Black	90079100	13,5 cm			
	Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Black	426 g	5,0 cm			
	MX-OPT-Box-3-EXT-ON-PW	4047438015103	33,5 cm	C	68,00	EUR
	Triple On-Wall-Housing, White	90079100	13,5 cm			
	Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: White	574 g	3,0 cm			
	MX-OPT-Box-3-EXT-ON-SV	4047438015141	33,5 cm	C	68,00	EUR
	Triple On-Wall-Housing, Silver	90079100	13,5 cm			
	Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Silver	574 g	3,0 cm			
	MX-OPT-Box-3-EXT-ON-BL	4047438015127	33,5 cm	C	68,00	EUR
	Triple On-Wall-Housing, Black	90079100	13,5 cm			
	Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Black	574 g	3,0 cm			
	MX-OPT-Box-3-EXT-IN	4047438015257	33,5 cm	C	28,00	EUR
	Triple In-Wall-Housing	90079100	13,5 cm			
	Suitable for: 3 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 318 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	362 g	3,0 cm			
	MX-OPT-Frame-4-EXT-PW	4047438017398	25,0 cm	C	118,00	EUR
	Quad Frame, White	90079100	25,0 cm			
	Suitable for: 4 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 233 x 233 x 18 mm (W x H x D) • Color: White	516 g	5,5 cm			
	MX-OPT-Frame-4-EXT-SV	4047438017435	25,0 cm	C	118,00	EUR
	Quad Frame, Silver	90079100	25,0 cm			
	Suitable for: 4 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 233 x 233 x 18 mm (W x H x D) • Color: Silver	516 g	5,5 cm			

	MX-OPT-Frame-4-EXT-BL	4047438017411	25,0 cm	C	118,00	EUR
	Quad Frame, Black	90079100	25,0 cm			
	Suitable for: 4 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 233 x 233 x 18 mm (W x H x D) • Color: Black	516 g	5,5 cm			
	MX-OPT-Box-4-EXT-ON-PW	4047438017442	25,0 cm	C	78,00	EUR
	Quad On-Wall-Housing, White	90079100	25,0 cm			
	Suitable for: 4 modules, outdoors • Metal-reinforced housing: 227 x 227 x 31 mm (W x H x D) • Color: White	620 g	5,5 cm			
	MX-OPT-Box-4-EXT-ON-SV	4047438017480	25,0 cm	C	78,00	EUR
	Quad On-Wall-Housing, Silver	90079100	25,0 cm			
	Suitable for: 4 modules, outdoors • Metal-reinforced housing: 227 x 227 x 31 mm (W x H x D) • Color: Silver	620 g	5,5 cm			
	MX-OPT-Box-4-EXT-ON-BL	4047438017466	25,0 cm	C	78,00	EUR
	Quad On-Wall-Housing, Black	90079100	25,0 cm			
	Suitable for: 4 modules, outdoors • Metal-reinforced housing: 227 x 227 x 31 mm (W x H x D) • Color: Black	620 g	5,5 cm			
	MX-OPT-Box-4-EXT-IN	4047438017497	25,0 cm	C	38,00	EUR
	Quad In-Wall-Housing	90079100	25,0 cm			
	Suitable for: 4 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 218 x 218 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	434 g	3,2 cm			
	MX-OPT-FlatMount-EXT-PW	4047438019811	14,7 cm	C	58,00	EUR
	FlatMount Frame, white	90079100	13,7 cm			
	For flush-mounting of MxDisplay and door station modules in wall cavities • Integrated electromagnetic theft protection • W x H: 124 x 124 mm • Color: white	190 g	5,5 cm			
	MX-OPT-FlatMount-EXT-BL	4047438019835	14,7 cm	C	58,00	EUR
	FlatMount Frame, black	90079100	13,7 cm			
	For flush-mounting of MxDisplay and door station modules in wall cavities • Integrated electromagnetic theft protection • W x H: 124 x 124 mm • Color: black	190 g	5,5 cm			
	MX-OPT-FlatMount-Box-EXT-IN	4047438019866	11,2 cm	C	18,00	EUR
	FlatMount Frame In-Wall Housing	90079100	11,2 cm			
	In-wall housing for FlatMount Frame • To be affixed securely with the subsurface or brick work • Size of cavity for flush-mounting (W x H x D): 112 x 112 x 60 mm	130 g	6,3 cm			

Building Automation Accessories

	Article No. / Name / Description	EAN / HS / weight	dimen.	DG	MSRP
	MX-AdminCard1	4047438015288	8,5 cm	C	8,00 EUR
	Admin RFID Transponder Card (Red)	85235290	5,5 cm		
	For system configuration IP Video Door Station via KeypadRFID and BellRFID • Type/encryption: MIFARE DESFire EV1 3K3DES/AES	2 g	0,1 cm		
	MX-UserCard1	4047438015295	8,5 cm	C	8,00 EUR
	User RFID Transponder Card (Blue)	85235290	5,5 cm		
	For keyless entry via with KeypadRFID or BellRFID (IP video door station) • Type/encryption: MIFARE DESFire EV1 3K3DES/AES	2 g	0,1 cm		
	MX-OPT-IO1	4047438013307	10,5 cm	C	148,00 EUR
	Extended Terminal Board (IO Module)	85299065	8,5 cm		
	Suitable for: T25M/T24M, delivers extended connection options for the door station (e.g., doorbell buttons, light, garage door opener, etc.) • Connect the IO Module to the camera module via MxBus, which connects it to the network. It has eight physical signal inputs that allow it to distinguish in AC operation between a pending full-wave and half-wave. This makes it possible to connect two switches to each signal input terminal so that 16 button inputs are made available. The inputs can be used for, e.g., bell buttons. The outputs can be used for external devices such as a doorbell, or for outdoor lights or garage door openers (via a power relay).	86 g	5,0 cm		
	MX-OPT-IO2	4047438014786	10,5 cm	C	28,00 EUR
	Ethernet Terminal Board	85299065	8,5 cm		
	Suitable for: T25M/T24M • The Ethernet terminal board is used to connect the door station for the T25 / T24 versions without Mx2wire+ technology. It securely connects the camera module with the 8 connected wires of the network patch cable via RJ45 connector. The Ethernet terminal board is screwed on to the housing (on-wall or in-wall) behind the camera module	58 g	5,0 cm		